

### product type designation

product description



### PROFIBUS plug, 90°, without PG socket

PROFIBUS bus connector, RS 485, Fast Connect, without programming port, 90°

SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, 15.8x 72.2x 36.4 mm (WxHxD), Insulation displacement method FastConnect, without PG socket

suitability for use

for connecting PROFIBUS nodes to the PROFIBUS bus cable

### transfer rate

transfer rate / with PROFIBUS DP

9.6 kbit/s ... 12 Mbit/s

### interfaces

number of electrical connections

- for PROFIBUS cables
- for network components or terminal equipment

2  
1

type of electrical connection

- for PROFIBUS cables
- for network components or terminal equipment

integrated insulation displacement contacts for 2-core PB FC-installation cables  
9-pin sub D connector

type of electrical connection / FastConnect

Yes

### mechanical data

design of terminating resistor

Resistor combination integrated and connectable via slide switch. Isolation function: When resistor is connected, outgoing bus is disconnected

material / of the enclosure

plastic

locking mechanism design

Screwed joint

### design, dimensions and weights

type of cable outlet

90 degree cable outlet

width

15.8 mm

height

72 mm

depth

36.4 mm

net weight

34 g

### ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-25 ... +60 °C  
-40 ... +70 °C  
-40 ... +70 °C

protection class IP

IP20

### product features, product functions, product components / general

product feature

- silicon-free

Yes

product component

- PG connection socket
- strain relief

No  
Yes

### standards, specifications, approvals

certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
reference code	
• according to IEC 81346-2	XF

### further information / internet-Links

Internet-Link	
• to website: Selection guide for cables and connectors	<a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a>
<b>last modified:</b>	7/7/2022 