



## Main

|                           |  |
|---------------------------|--|
| Range of Product          | Harmony XVS                                |
| Product or Component Type | Siren                                      |
| Device short name         | XVS  |
| Color                     | White                                      |
| Signalling type           | 2 tones siren                              |
| [Us] rated supply voltage | 120 V AC                                   |
| Noise level               | 106 dB continuous or intermittent tone)1 m |

## Complementary

|  |                                     |
|--|-------------------------------------|
| Material                               | PC body                             |
| Net Weight                             | 2.20 lb(US) (1 kg)                  |
| Marking                                | CE                                  |
| [Uimp] rated impulse withstand voltage | 4 kV                                |
| Current consumption                    | 80 mA 120 V                         |
| Clamping connection capacity           | <= 1 x 1.5 mm <sup>2</sup>          |
| Electrical connection                  | Cable 0.26...0.33 in (6.5...8.5 mm) |
| Width                                  | 4.49 in (114 mm)                    |
| Height                                 | 4.49 in (114 mm)                    |
| Depth                                  | 6.03 in (153.2 mm)                  |

## Environment

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1 |
| Protective treatment                  | TC                                 |
| Ambient Air Temperature for Storage   | -31...158 °F (-35...70 °C)         |
| Ambient air temperature for operation | -22...122 °F (-30...50 °C)         |
| Electrical shock protection class     | Class II EN/IEC 61140              |
| IP degree of protection               | IP53                               |

## Ordering and shipping details

|                       |                          |
|-----------------------|--------------------------|
| Category              | 22617 - XVC TOWER LIGHTS |
| Discount Schedule     | XV                       |
| GTIN                  | 3389119045353            |
| Nbr. of units in pkg. | 1                        |
| Package weight(Lbs)   | 2.7 lb(US) (1.22 kg)     |
| Returnability         | No                       |
| Country of origin     | ID                       |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 5.51 in (14 cm)         |
| Package 1 width              | 5.51 in (14 cm)         |
| Package 1 Length             | 7.87 in (20 cm)         |
| Unit Type of Package 2       | S04                     |
| Number of Units in Package 2 | 8                       |
| Package 2 Weight             | 24.78 lb(US) (11.24 kg) |
| Package 2 Height             | 11.81 in (30 cm)        |
| Package 2 width              | 15.75 in (40 cm)        |
| Package 2 Length             | 23.62 in (60 cm)        |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Siren

Dimensions

