

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		QT	AT
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾			
	VOLTAGE	125 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %			
	CURRENT	0.5 A	STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾			
SPECIFICATIONS							
ITEM	TEST METHOD		REQUIREMENTS		QT	AT	
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.		x	x	
MARKING		CONFIRMED VISUALLY.			x	x	
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	45 mΩ MAX.	x	—			
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)	55 mΩ MAX.	x	—			
MILLIVOLT LEVEL METHOD							
INSULATION RESISTANCE	250 V DC.	100 MΩ MIN.	x	—			
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	x	—			
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION		500 TIMES INSERTIONS AND EXTRactions.	① CONTACT RESISTANCE: 55 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x	—	
VIBRATION	FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.52 mm, AT 2 h FOR 3 DIRECTION.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x	—		
SHOCK	490 ms ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			x	—		
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.	① CONTACT RESISTANCE: 55 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN.		x	—		
RAPID CHANGE OF TEMPERATURE	TEMPERATURE:-55→+15~+35→+85→+15~+35°C TIME 30 → 10~15 → 30 → 10~15 min UNDER 5 CYCLES.	③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x	—		
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 55 mΩ MAX. ② NO HEAVY CORROSION.		x	—		
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)			x	—		
RESISTANCE TO SOLDERING HEAT	1) SOLDER BATH:SOLDER TEMPERATURE, 260±5°C. FOR IMMERSION,DURATION,10±1s. 2) SOLDERING IRONS : 360°C. FOR 5 s.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.		x	—		
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE 240±3°C. FOR IMMERSION DURATION, 2s.	A NEW UNIFORM COATING OF SOLDER SHALL OVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.		x	—		
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
△							
REMARK ⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.							
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-082376-21			
HRS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO.		FX2B-60P-1. 27DSAL (71)	
		CODE NO.		CL572-0855-3-71		△	
						1/1	