


In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ^②
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ^①		OPERATING HUMIDITY RANGE	40 % TO 80 %
	VOLTAGE	100 V AC		STORAGE HUMIDITY RANGE	40 % TO 70 % ^②
	CURRENT	0.4 A			
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	Q/T	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	45 m Ω MAX.	X	-	
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)	55 m Ω MAX.	X	-	
MILLIVOLT LEVEL METHOD					
INSULATION RESISTANCE	250 V DC	100 M Ω MIN.	X	-	
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-	
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION	50 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 55 m Ω MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
VIBRATION	FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.5 mm, 2h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μ s. ② CONTACT RESISTANCE: 55 m Ω MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
SHOCK	490 m/s ² , DURATION OF PULSE 11 ms FOR 3 TIMES IN 3 DIRECTIONS.		X	-	
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 \pm 2 °C, 90 ~ 95 %, 96 h	① CONTACT RESISTANCE: 55 m Ω MAX. ② INSULATION RESISTANCE: 100 M Ω MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: -55 \rightarrow +15 \sim +35 \rightarrow +85 \rightarrow +15 \sim +35 °C TIME 30 \rightarrow 2 \sim 3 \rightarrow 30 \rightarrow 2 \sim 3 min 5 CYCLES.		X	-	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 55 m Ω MAX. ② NO HEAVY CORROSION.	X	-	
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)		X	-	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	-	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE: 240 °C, FOR IMMERSION DURATION, 3 s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.	X	-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
REMARK ^① TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ^② THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.	APPROVED	HS. OKAWA		05.11.24	
	CHECKED	HS. OZAWA		05.11.24	
	DESIGNED	TK. YANAGISAWA		05.11.22	
	DRAWN	TK. YANAGISAWA		05.11.22	
Note QT: Qualification Test AT: Assurance Test X: Applicable Test		DRAWING NO.	ELC4-150569-25		
HRS		SPECIFICATION SHEET		PART NO.	FX8-60P-SV1 (71)
		HIROSE ELECTRIC CO., LTD.		CODE NO.	CL578-0041-0-71
					 1/1