



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 <sub>4</sub>	REVISED	5/28/86 5/27/86	<i>[Signature]</i>

NOTES:

- 1. CAPTURED CENTER CONTACT

.XXX = in  
XX.X = mm

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT EXT BUSHING	IRON-NICKEL-COBALT ALLOY PER MIL-I-23011 CLASS 1 (KOVAR)	GOLD PLATE PER MIL-G-45204
HERMETIC SEAL	GLASS BEAD	N/A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRAC. ± 1/64 DEC. ± .005 ANGLES ± 1°	DRAWN BY N.K.	DATE 2/11/86	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY J.J.	3/17/86	
APPD BY R.V.	3/27/86	<b>AMP</b>	
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE "OSM", PANEL FEEDTHROUGH, JACK RECEPTACLE, KNIFE EDGE, HERMETIC SEAL	
	NO. A.P. 408-04851 (20-607)	SIZE B	CODE IDENT NO. 26805
		2058-5219-00	REV 01 <sub>4</sub>
	SCALE 8:1	SHEET 1 OF 1	

RECOMMENDED MOUNTING HOLE  
SCALE 4:1