## ATGBICS SFP-10G-ZR-D Cisco Compatible Transceiver SFP+ 10GBase-BX-D (Tx1550nm/Rx1490nm, 80km, SMF, DOM)

**Brand :** ATGBICS **Product code:** SFP-10G-ZR-D-C

**Product name :** SFP-10G-ZR-D Cisco Compatible Transceiver SFP+ 10GBase-BX-D (Tx1550nm/Rx1490nm,

80km, SMF, DOM)

SFP-10G-ZR-D Cisco Compatible Transceiver SFP+ 10GBase-BX-D (Tx1550nm/Rx1490nm, 80km, SMF, DOM)

 $ATGBICS\ SFP-10G-ZR-D\ Cisco\ Compatible\ Transceiver\ SFP+\ 10GBase-BX-D\ (Tx1550nm/Rx1490nm,\ 80km,\ SMF,\ DOM):$ 

ATGBICS SFP-10G-ZR-D 1000Base-BX SFP supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of Tx1550nm/Rx1490nm via an LC connector. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of CiscoSFP-10G-ZR-D= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Power	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 10000 Mbit/s  Interface type * SFP+  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector  SFP transceiver standard  Maximum transfer distance  Tx wavelength (max)  Rx wavelength (max)  Ethernet LAN	10000 Mbit/s SFP+	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
	LC BX-D 80000 m 1550 nm	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
		Weight & dimensions	
Ethernet interface type Digital Diagnostics Monitoring (DDM)	10 Gigabit Ethernet  ✓	Width Depth Height	13.4 mm 56.5 mm 8.5 mm
Features		Weight	19 g
Product colour	Silver	Packaging data	
Housing material Metal Plug and Play		Number of products included Package type	1 pc(s) Box
Hot-swap  Fasy to install	sy to install  untry of origin  und compatibility  United Kingdom  Cisco	Technical details	
Country of origin Brand compatibility Certification		Sustainability compliance Sustainability certificates Doesn't contain	√ RoHS Lead



5056468719799

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.