



- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
  2. Albaloy Plating (Copper-Tin-Zinc) Pl. 80 Min, Thick
  3. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick
  4. Teflon
  5. Passivated

Crimped Ferrule  
 Hex. Crimp Size .213 (5.4)  
 Crimped Contact Pin  
 Hex. Crimp Size .100 (2.54)

RoHS Compliant

9	Ferrule	Note 1	Note 2	1
8	Contact Pin	Note 1	Note 3	1
7	Retainer Ring	SUS 304	Note 5	1
6	Gasket	Silicone	Red	1
5	Contact Body	Note 1	Note 2	1
4	Insulator	Note 4	Natural	1
3	Barrel	Note 1	Note 2	1
2	Body	Note 1	Note 2	1
1	Shell	Note 1	Note 2	1

Dimensions are in Inches  
 Unless Otherwise Specified  
 Tolerances  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

Part No.	
Approved	Date 12-14-2018
Checked	Date 12-14-2018
Drawn	Date 12-14-2018

<b>NTE Electronics</b>	
Title	N Crimp Plug (For RG-58C/U Cable)
Drawing No.	06-N002
File No.	

No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	2.5/1	Issue	A
-----	-------------	----------	--------	------	-------------	-------	-------	-------	---