



## Introducing WM-SCE Heat-shrinkable Wrap-around Marker for Cable Identification

TE Connectivity's (TE) newest heat-shrinkable wrap-around marker is designed for permanent cable identification. The thin and flexible wrap-around marker has a hot melt adhesive on the reverse side that when heat activated creates a permanent bond at the point where the material overlaps. As the wrap-around marker is made of a radiation cross-linked polyolefin, the material will shrink upon heat activation to conform to the contours of any substrate.

### KEY FEATURES

- Heat-shrinkable wrap-around
- Color: white
- Hot-melt adhesive for a permanent bond
- Thermal transfer printable
- Post termination / retrofit suitable
- Extremely durable and resistant to harsh environments

### APPLICATIONS

Used for small and large diameter cable, harness, hose and pipe identification in the following industries:

- Aerospace
- Defense
- Marine
- Industrial
- Commercial
- Railway & Mass Transit

The wrap-around marker is ideal for post termination applications and retrofit saving the customer from the labor intensive processes of disconnecting the cable, conduit, or hose assembly prior to install. The wrap-around marker can be used in harsh outdoor and industrial environments, where resistance to mechanical abrasion and fluid exposure is a must. The marker is supplied on 100 feet (30.5 m) rolls and can be printed and cut to desired lengths.

The heat-shrinkable wrap-around marker allows permanent marking on small and large diameter cables, hoses, pipes or harnesses, and can truly be applied at any stage of the build (i.e. pre or post termination).

### MATERIALS

The marker is fabricated of irradiated, thermally stabilized and flame retarded modified polyolefin compound with a hot melt adhesive coating on one side.

### TE CONNECTIVITY SPECIFICATIONS

- TTDS-244
- RW-2532

### STANDARDS

- Mark adherence: in accordance to SAE-AS 5942
- Solvent resistance: in accordance with MIL-STD-202G method 215K

### PRODUCT OFFERING

WM-SCE-48.2-9

### DIMENSIONS

- Width: 48.2 mm (1.9 in)
- Thickness: 0.56 mm (0.022 in) - uninstalled
- Spool length: 30.5 m (100 feet)

**SAMPLES NOW AVAILABLE**

[te.com/products/identification-labeling](http://te.com/products/identification-labeling)





The WM-SCE heat-shrinkable wrap-around marker can be used on a variety of substrates, and will conform to cables as small as 6.4 mm (0.25 in) O.D.



The WM-SCE heat-shrinkable wrap-around marker can be installed on 'live circuits' as well.

## INSTALLATION INSTRUCTIONS

Document 411-121004 (WM-SCE Installation Guide)

## QUALIFIED PRINTERS, RIBBONS AND SOFTWARE

### Printers

Part number	Description
<b>CR2120-000</b>	TE3112-PRINTER
<b>CC9352-000</b>	TE3124-PRINTER
<b>CC7246-000</b>	T2000CT-PRINTER
<b>TE-PRINTER-PERFORATOR</b>	Cutter/perforator

### Ribbon

Part number	Description
<b>F55931-000</b>	1966-RIBBON

### Software

Part number	Description
<b>ED4097-000</b>	WINTOTAL-5-DONGLE
<b>ED4098-000</b>	WINTOTAL-5-LICENCE

## SAMPLES NOW AVAILABLE

While TE has made every reasonable effort to ensure the accuracy of the information in this flyer, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this flyer are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

[te.com/products/identification-labeling](http://te.com/products/identification-labeling)

