Instant GUI 3.5" Touch Screen LCD Kit



uEZGUI-RX62N-35QT for Renesas RX600 Family





Features

- Tianma 3.5" TFT QVGA Touch Screen LCD (320x240)
- Renesas RX621/RX62N CPU with up to 512KB internal Flash
- USB Device Mini-B for power and PC communications
- 2MB SDRAM
- 2GB microSD Memory Card
- On-board Speaker
- Mini-JTAG Debug Connector
- Actual Size: 3.1" x 3.05" x 0.54"
- External Expansion via 50-pin I/O Connector
 - o Serial Ports, UART, I2C, SPI, USB Host/Device



Software

- uEZ[®] / FreeRTOS Rapid Development Platform
- MicroSD card maps as USB Flash Drive to the PC
- Renesas HEW Compiler and Tool Suite
- Segger J-Link Lite JTAG for programming and debug
- MIDI Player

Part





RENESAS







The **uEZGUI-RX62N-35QT** includes a 96MHz Renesas RX621 or RX62N microcontroller running the open source uEZ® + FreeRTOS software platform. The RX62N has 512KB of internal Flash memory, 96KB of internal SRAM, a 10/100 Ethernet Media Access Controller (MAC), a USB full speed device/host/OTG controller, up to six UARTs, one CAN channels and a collection of serial communications interfaces.

Software Included

 $\mu EZ^{\mathbb{R}}$ (pronounced Muse) is an open source rapid development platform that supplies application developers with an extensive library of open source software, drivers, and processor support - all under a common framework. $\mu EZ^{\mathbb{R}}$ allows companies to focus on innovation and their value-added applications while minimizing development time and maximizing software reuse.


The diagram below shows a typical embedded application stack. The $\mu EZ^{\mathbb{R}}$ components comprise three primary categories to simplify embedded application development:

- Operating System Abstraction Layer ($\mu EZ^{\mathbb{R}} OSAL$)
- Sub-system drivers (ex: $\mu EZ^{\mathbb{R}}$ TCP/IP, $\mu EZ^{\mathbb{R}}$ USB, $\mu EZ^{\mathbb{R}}$ Driver)
- Hardware Abstraction Layer ($\mu EZ^{\mathbb{R}}$ HAL)

Warranty: 30-day money back guarantee

Fax 256-883-1241

Phone 256-883-1240



The **uEZGUI-RX62N-35QT** is designed to be used as an "off-the-shelf" Graphical User Interface (GUI) or Human Machine Interface (HMI) in a variety of end customer applications. The miniature, self-contained design is well suited to embed directly into your product or FDI offers prepackaged versions for stand-alone use (for example, the **uEZGUI-RX62N-35QT-BA** FDI also offers low cost customization services

for customer specific hardware, software or packaging applications at volumes of 500 units or more.

Ordering Information Kit Contents: Part Number: uEZGUI-RX62N-35QT - uEZ[®] GUI 3.5" Board with RX62N - Tianma 3.5" QVGA Touch Screen LCD

- USB Device cable for Power and PC communications
- Mini JTAG Debugger with cables

