

2019



wiha 

Tools that work for you

# PROFESSIONAL TORQUE CONTROL







## COMPLETE TORQUE CONTROL PROGRAM




TorqueFix • TorqueVario • TorqueControl Blades • TorqueFix Wing EasyTorque • iTorque • Adapters • Cable Keys • Insulated TorqueVario ESD Safe TorqueVario • T-handle Torque • TorqueControl Sets • Micro Bits



**Wiha TorqueFix Wing Handles & Blades**

DESCRIPTION	Page
 TorqueFix Handle	4
 Hex Metric Blades	4
 TORX Blades	4
 TORXPlus Blades	4


**Wiha TPMS Install / Repair Kit**

DESCRIPTION	Page
 TPMS Set	4

**Wiha TorqueControl Tools**

DESCRIPTION	Page
 TorqueFix Handle	5
 TorqueVario Handle	5
 TorqueVario Handle (Newton Meter Scale)	5
 Standard Blades Slotted, Phillips, Torx®, TorxPlus®, Hex	6
 MicroBits Slotted, Phillips, Torx®, Security Torx® Hex, Security Hex, Pentalobe & Nut Setters	9
 TorqueControl Sets	10-11



**Wiha TorqueControl Blades & Bits**

DESCRIPTION	Page
 Standard Blades Slotted, Phillips, Torx®, TorxPlus®, Hex	6
 MicroBits Slotted, Phillips, Torx®, Security Torx® Hex, Security Hex, Pentalobe & Nut Setters	9



**Wiha EasyTorque Handles**

DESCRIPTION	Page
 EasyTorque Handles	7
 EasyTorque TORX	7
 EasyTorque TORXPlus	7





**Wiha iTorque Handles & Sets**

DESCRIPTION	Page
 iTorque Handles	8
 iTorque Sets	8

**Wiha TorqueControl Accessories**

DESCRIPTION	Page
 TorqueControl Adapters	6-7
 Torque Cable Key	7

**Wiha Torque SlimLine Insulated Tools**

DESCRIPTION	Page
 TorqueVario Handle	12
 Insulated Blade Holder	13
 Insulated SlimLine Blades Slotted, Phillips, Terminal, TORX, Square	13
 Ins. Torque SlimLine Sets	12



## Wiha TorqueFix Wing Keys Handles & Blades

- Audible Click At Torque
- Replaceable Blades
- +/- 6% Repeatability
- Extremely Compact
- Quick Turning Zone



Low profile  
for easy access

Small &  
Compact

Very slim blade diameter for  
hard to reach screws

Torque tool for very tight  
machine assembly spaces



EN ISO 6798,  
BS EN 26789, ASME  
B107.14M

+/- 6% Accuracy



Includes Calibration  
Certificate

### 283 TorqueFix Wing Handles

Audible & perceptible click when torque setting  
has been attained.

Item No.	Nm	mm	Inch	pkg.	lbs.
28349	0.5	68	2.7	1	.28
28351	0.6	68	2.7	1	.28
28352	0.9	68	2.7	1	.28
28353	1.1	68	2.7	1	.28
28354	1.2	68	2.7	1	.28
28355	1.4	68	2.7	1	.28
28356	2.0	68	2.7	1	.28
28357	2.5	68	2.7	1	.28
28358	3.0	68	2.7	1	.28
28359	3.8	68	2.7	1	.28
28360	4.0	68	2.7	1	.28



### 283 TORX® Blades For TorqueFix

Wing Handles CVM steel, through-hardened,  
titanium silver.

Item No.	Size	Max Nm	Inch	pkg.	lbs.
28374	T6	0.6	3.0	1	.03
28375	T7	0.9	3.0	1	.03
28376	T8	1.3	3.0	1	.03
28377	T9	2.5	3.0	1	.03
28378	T10	3.8	3.0	1	.03
28379	T15	5.5	3.0	1	.03
28380	T20	8.0	3.0	1	.03
28381	T25	8.0	3.0	1	.03



### 283 TORXPlus® Blades For TorqueFix

Wing Handles CVM steel, through-hardened,  
titanium silver.

Item No.	Size	Max Nm	Inch	pkg.	lbs.
28382	IP6	0.8	3.0	1	.03
28383	IP7	1.3	3.0	1	.03
28384	IP8	2.0	3.0	1	.03
28385	IP9	3.0	3.0	1	.03
28386	IP10	4.5	3.0	1	.03
28387	IP15	6.6	3.0	1	.03
28388	IP20	8.0	3.0	1	.03
28389	IP25	8.0	3.0	1	.03



### 283 Hex Metric Blades For TorqueFix

Wing Handles CVM steel, through-hardened,  
titanium silver.

Item No.	Size	Max Nm	Inch	mm	lbs.	pkg.
28361	1.5	0.9	3.0	75	.03	1
28362	2.0	1.8	3.0	75	.03	1
28363	2.5	3.8	3.0	75	.03	1
28364	3.0	5.5	3.0	75	.03	1
28365	4.0	8.0	3.0	75	.03	1



**Wiha Adjustable TorqueControl Tools**

**Wiha TorqueControl Screwdrivers**

- **TorqueFix** factory preset torque
- **TorqueVario** adjustable torque drivers

*molded cushion grip two component handles allow for maximum achievable torque to be reached with comfort.*


**Precise repeatability!**

**All TorqueFix & TorqueVario tools are tested and comply with:**

- **EN ISO 6789**
- **BS EN 26789**
- **ASME B107.14M**

**Each tool has unique serial number and certificate of calibration**

Whether it's TorqueVario-S or TorqueFix - Wiha has a torque screwdriver to cover almost every application



+/-6% accuracy tolerance  
Certificate of calibration



**285 TorqueFix, With Wiha-SoftFinish®**  
**Handle** Fixed Torque value pre-set. Tested in accordance with EN ISO 6789, BS EN 26789, ASME B107.14M, tolerance +/- 6%. Audible & perceptible click when pre-set torque has been attained. Automatically resets for next torque cycle; 50% greater reverse torque.

Item No.	Pre-Sets		Torque				Pkg.
	oz.	lbs.	Nm	mm	Inch	lbs.	
28503	80	5	0.56	112	4.4	.16	1
28505	120	7.5	0.84	112	4.4	.15	1
28507	160	10	1.12	119	4.7	.28	1
28509	200	12.5	1.41	119	4.7	.27	1
28511	240	15	1.69	119	4.7	.27	1
28513	320	20	2.25	119	4.7	.28	1
28515	400	25	2.82	126	4.9	.37	1
28517	480	30	3.39	126	4.9	.37	1
28518	560	35	3.95	126	4.9	.37	1
28519	640	40	4.52	126	4.9	.37	1
28521	800	50	5.65	132	5.2	.52	1
28523	960	60	6.78	132	5.2	.52	1
28525	1120	70	7.91	132	5.2	.52	1

Direct Reading Scale



4mm Bit Holder

+/-6% accuracy tolerance Certificate of calibration

**285 Adjustable TorqueVario With Direct Reading Scale** EN ISO 6789, BS EN 26789, ASME B107.14M. Ergonomic molded multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible and perceptible click when the torque setting has been attained, automatically resets for next torque cycle.

Item No.	Range		Increments		Pkg.
	Inch	lbs.	mm	lbs.	
28501*	15 - 80	(in/oz)	2.5 In.oz.	127	.22
28502	5 - 10		.5 In.lbs.	127	.41
28506	10 - 50		2 In.lbs.	138	.59

\* 28501 +/- 10% (This unit only)\*

Item No.	Range		Increments		Pkg.
	Inch	lbs.	mm	lbs.	
28404	5 - 18		1 In.lbs.	131	.50
28408	18 - 62		2 In.lbs.	142	.74

Direct Reading Scale



1/4" Bit Holder

Item No.	Range		Increments		Pkg.
	Inch	lbs.	mm	lbs.	
28410*	15 - 80	(in/oz)	2.5 In.oz.	127	
28411	5 - 10		.5 In.lbs.	127	
28412	10 - 50		2 In.lbs.	138	
28413	5 - 18		.5 In.lbs.	131	
28414	18 - 62		2 In.lbs.	142	

+/-6% accuracy tolerance Certificate of calibration

\* 28501 +/- 10% (This unit only)

+/-6% accuracy tolerance  
Certificate of calibration



**285 Adjustable TorqueVario-S Handle - In Newton Meter Scale** EN ISO 6789, BS EN 26789, ASME B107.14M. Ergo molded multi-component handle, light & compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when the torque setting has been attained, automatically resets for next torque cycle.

Item No.	Newton Meter Scale		Increments		Pkg.
	mm	lbs.	mm	lbs.	
28550*	0.1 - 0.6	Nm	.05 Nm	127	.35
28551	0.4 - 1.0	Nm	.05 Nm	127	.35
28552	0.5 - 2.0	Nm	.10 Nm	131	.45
28553	0.8 - 5.0	Nm	.20 Nm	138	.55
28655	2.0 - 7.0	Nm	.25 Nm	142	.70

\* +/- 10% (This unit only)


+/-6% accuracy tolerance  
Certificate of calibration



1/4" Bit Holder

Item No.	Range		Increments		Pkg.
	Inch	lbs.	mm	lbs.	
28415*	0.1 - 0.6	Nm	.05 Nm	127	
28416	0.4 - 1.0	Nm	.05 Nm	127	
28417	0.5 - 2.0	Nm	.10 Nm	131	
28418	0.8 - 5.0	Nm	.20 Nm	138	
28419	2.0 - 7.0	Nm	.25 Nm	142	

\* +/- 10% (This unit only)



All TorqueVario models include Torque setting adjustment tool

## Wiha TorqueControl Blades - For Easy Torque, TorqueFix & TorqueVario Handles



**285 Slotted Interchangeable Blades For TorqueFix & TorqueVario** Slotted tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item				Max.		
No.	mm	Inch	mm	lbs.	Nm	pkg.
28534	1.5	.059	175	.07	0.15	1
28535	2.0	.078	175	.07	0.4	1
28536	2.5	.098	175	.07	0.4	1
28537	3.0	.118	175	.07	0.6	1
28538	3.5	.139	175	.07	1.1	1
28539	4.0	.157	175	.07	2.5	1



**285 Phillips Interchangeable Blades For TorqueFix & TorqueVario** Phillips tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

Item				Max.		
No.	Size	mm	mm	lbs.	Nm	pkg.
28540	000	175	4.0	.07	0.4	1
28541	00	175	4.0	.07	0.4	1
28542	0	175	4.0	.07	0.9	1
28543	1	175	4.0	.07	3.8	1
28544	2	175	4.0	.07	5.5	1



**285 TORX® Interchangeable Blades For TorqueFix & TorqueVario** TORX® tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item				Max.		
No.	Size	mm	mm	lbs.	Nm	pkg.
28561	T5	175	4.0	.07	0.4	1
28562	T6	175	4.0	.07	0.6	1
28563	T7	175	4.0	.07	0.9	1
28564	T8	175	4.0	.07	1.3	1
28565	T9	175	4.0	.07	2.5	1
28566	T10	175	4.0	.07	3.8	1
28567	T15	175	4.0	.07	5.5	1
28568	T20	175	4.0	.07	8.0	1
28569	T25	175	4.0	.07	8.0	1



**285 Hex Inch Interchangeable Blades For TorqueFix & TorqueVario** Hex tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item				Max.	
No.	Inch	mm	lbs.	Nm	pkg.
28555	.050	175	.07	.4	1
28556	1/16	175	.07	.9	1
28557	5/64	175	.07	1.8	1
28558	3/32	175	.07	1.8	1
28559	7/64	175	.07	3.8	1
28560	1/8	175	.07	5.5	1
28587	9/64	175	.07	8.0	1
28588	5/32	175	.07	8.0	1



**285 Hex Metric Interchangeable Blades For TorqueFix & TorqueVario** Hex tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item				Max.	
No.	mm	mm	lbs.	Nm	pkg.
28545	1.5	175	.07	0.9	1
28546	2.0	175	.07	1.8	1
28547	2.5	175	.07	3.8	1
28548	3.0	175	.07	5.5	1
28549	4.0	175	.07	8.0	1



**285 TORXPlus® Blades For TorqueFix & TorqueVario** TORXPlus® tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item				Max.		
No.	Size	mm	mm	lbs.	Nm	pkg.
28571	IP5	175	4.0	.07	0.5	1
28572	IP6	175	4.0	.07	0.8	1
28573	IP7	175	4.0	.07	1.3	1
28574	IP8	175	4.0	.07	2.0	1
28575	IP9	175	4.0	.07	3.0	1
28576	IP10	175	4.0	.07	4.5	1
28577	IP15	175	4.0	.07	6.6	1
28578	IP20	175	4.0	.07	8.0	1
28579	IP25	175	4.0	.07	8.0	1



**285 MagicSpring TORX® Interchangeable Blades For TorqueFix & TorqueVario** blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item				Max.		
No.	Size	mm	mm	lbs.	Nm	pkg.
28512	T6	175	4.0	.07	0.6	1
28527	T7	175	4.0	.07	0.9	1
28528	T8	175	4.0	.07	1.3	1
28529	T9	175	4.0	.07	2.5	1
28530	T10	175	4.0	.07	3.8	1
28531	T15	175	4.0	.07	5.5	1
28532	T20	175	4.0	.07	8.0	1
28533	T25	175	4.0	.07	8.0	1



**286 MagicSpring TORXPlus® Interchangeable Blades For TorqueFix & TorqueVario** blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item				Max.		
No.	Size	mm	mm	lbs.	Nm	pkg.
28611	IP6	175	4.0	.07	0.8	1
28612	IP7	175	4.0	.07	1.3	1
28613	IP8	175	4.0	.07	2.0	1
28614	IP9	175	4.0	.07	3.0	1
28616	IP10	175	4.0	.07	4.5	1
28617	IP15	175	4.0	.07	6.6	1
28618	IP20	175	4.0	.07	8.0	1
28619	IP25	175	4.0	.07	8.0	1

\*None of the blades featured on this page will function in a TorqueVario Insulated Handle

## Wiha TorqueControl Adapters



**28882 ESD Safe Bit Holder Adapter For 1/4" Drive Bits**

Shaft CVM steel, hardened, corrosion protected. (Not for use in Insulated handles)

Item				Max.	
No.	Size	mm	mm	lbs.	pkg.
28882	1/4	162	4.0	.09	1

### Wiha Torque Cable Keys

Torque handles recommended  
#28552 & #28504



#### 286 Torque Cable Key For Threaded Hex Connectors

For torque controlled fastening of cable plug connectors with Hex heads. Used with Wiha-TorqueControl Screwdrivers.

Item No.	Size	mm	mm	mm	Max Nm	lbs.	pkg.
28620	8mm	4.0	78	218	1.0	.06	1
28622	9mm	4.0	78	218	1.0	.06	1
28624	11mm	4.0	78	218	1.5	.06	1
28626	12mm	4.0	78	218	1.5	.06	1
28627	13mm	4.0	78	218	1.5	.06	1
28629	14mm	4.0	78	218	1.5	.06	1
28632	17mm	4.0	78	218	1.5	.06	1
28633	18mm	4.0	78	218	1.5	.06	1
28637	22mm	4.0	90	233	2.0	.10	1



#### 28644 Torque Cable Key For Threaded Hex Connectors - Inch

Item No.	Size	mm	mm	mm	Max Nm	lbs.	pkg.
28644	1/2"	4.0	78	218	1.5	.06	1

### easyTorque Control Handles

## "easy" Torque

- Audible Click At Torque
- Replaceable Blades
- +/- 10% Repeatability
- Improve Productivity
- Reduces Waste
- Controls Costs
- Save Time!



Each tool factory preset

Torque accuracy of +/- 10% to 5000 cycles

Economical Torque Control for tooling assembly and repair

Reverse torque is 50% greater for easy removal using same tool

Uses 285 Series interchangeable blades on pg. 6



#### 292 easyTorque Screwdriver Handle

easyTorque value pre-set. Release accuracy +/- 10%. SoftFinish cushion grip handle for good power transfer.

Item No.	Pre-Sets Inch/lbs.	Nm	mm	Inch	lbs.	pkg.
29205	4.4	0.5	130	5.1	.20	1
29206	5.3	0.6	130	5.1	.20	1
29209	8.0	0.9	130	5.1	.20	1
29211	9.7	1.1	130	5.1	.20	1
29212	10.6	1.2	130	5.1	.20	1
29214	12.4	1.4	130	5.1	.20	1
29220	17.7	2.0	130	5.1	.20	1
29225	22.1	2.5	130	5.1	.20	1
29230	26.6	3.0	130	5.1	.20	1
29238	33.6	3.8	130	5.1	.20	1
29241	35.4	4.0	130	5.1	.20	1
29245	39.8	4.5	130	5.1	.20	1
29251	44.2	5.0	130	5.1	.20	1

\* No Calibration Certificates



#### 292 easyTorque Screwdriver Handle With TORX® Blades

easyTorque value pre-set. Release accuracy +/- 10%. Internal mechanism clicks when torque value has been attained. Cushion grip comfortable handle for good power transfer.

Item No.	Pre-Sets Size	Inch/lbs.	Nm	lbs.	pkg.
29232	T5	4.4	0.5	.24	1
29233	T6	5.3	0.6	.24	1
29234	T7	8.0	0.9	.24	1
29236	T8	10.6	1.2	.25	1
29237	T9	12.4	1.4	.25	1
29239	T10	17.7	2.0	.26	1
29242	T15	26.6	3.0	.26	1
29243	T20	35.4	4.0	.26	1
29244	T25	44.2	5.0	.28	1

\* No Calibration Certificates



#### 292 easyTorque Screwdriver Handle With TORXPlus® Blades

easyTorque value pre-set. Release accuracy +/- 10%. Internal mechanism clicks when torque value has been attained. Cushion grip comfortable handle for good power transfer.

Item No.	Pre-Sets Size	Inch/lbs.	Nm	lbs.	pkg.
29246	IP5	4.4	0.5	.24	1
29247	IP6	5.3	0.6	.24	1
29248	IP7	8.0	0.9	.24	1
29249	IP8	10.6	1.2	.25	1
29252	IP9	12.4	1.4	.25	1
29253	IP10	17.7	2.0	.26	1
29254	IP15	26.6	3.0	.26	1
29255	IP20	35.4	4.0	.26	1
29256	IP25	44.2	5.0	.28	1

\* No Calibration Certificates

### Wiha TorqueControl Adapters

#### Adapters For TorqueFix™ & TorqueVario™



**28581 Bit Holder Adapter For 1/4" Drive Bits** Shaft CVM steel, hardened, corrosion protected. (Not for use in Insulated handles)

Item No.	Size	mm	mm	lbs.	pkg.
28581	1/4	149	4.0	.09	1



**28582 Square Drive Adapter For 1/4" Sockets** Shaft CVM steel, hardened, corrosion protected. (Not for use in Insulated handles)

Item No.	Size	mm	mm	lbs.	pkg.
28582	1/4	145	4.0	.08	1



**28583 Adapter Blade For 4mm MicroBits** Shaft CVM steel, hardened, corrosion protected. (Not for use in Insulated handles)

Item No.	Size	mm	mm	lbs.	pkg.
28583	4.0	149	4.0	.09	1

## Wiha TorqueControl Adjustable iTorque

### iTorque Screwdrivers

- Metric (Nm) & Inch (In-lbs / oz)
- Built in click counter
- Auto shut off
- Fast adjusting
- Cycle Counter
- Accurate +/- 6%



Digital Torque Control

Interchangeable blades or bits

With Certificate of Calibration Included



4mm bit holder included

#### 288 iTorque Screwdriver Handles

EN ISO 6789, BS EN 26789, ASME B107.14M. Handle reads Nm & Inch/lbs. with built in click counter. Fast adjusting. Accurate +/- 6% Each iTorque handle includes a 4mm bit holder.

Item No.	Adjustable Maximum Torque	Adjustable	pkg. 1		
			mm	Inch	lbs.
28886	60-210(in/oz.)	40-150(Ncm)	134	5.3	.44
28887	7-26 in/lbs.	0.8-3.0 Nm	134	5.3	.44
28889	9-45 in/lbs.	1.0-6.0 Nm	134	5.3	.44

\* Calibration Certificates Included



Quick Adjusting

Digital Display

Push Button Start Push Button Conversion

Fast Conversion Nm to In/lbs.

With Certificate of Calibration



#### 52 Pc. Set

**28891 52 Piece iTorque Bit Set, In Metal Storage Box** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable iTorque handle 60-210 in/oz. 40-150 Ncm, 50 insert bits & 1/4" bit holder.

Item	Slotted: 4.5, 5.5, 6.5, 8.0mm
No.	Phillips: #0, #1, #2, #3
28891	TORX®: T6, T7, T8, T9, T10, T15, T20, T25, T27, T3
lbs.	Hex Inch: 1/16, 5/64, 3/32, 7/64, 1/8, 2.56 9/64, 5/32, 3/16"
	Hex Metric: 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm
	Pozidriv: #0, #1, #2, #3
	Torq Set: #4, #5, #6, #8
	Square: #1, #2, #3
	Triwing: #0, #1, #2, #3, #4
	iTorque Handle Range 60 - 210 Inch/oz. 28581 - 1/4" Bit Holder

With Certificate of Calibration



#### 52 Pc. Set

**28892 52 Piece iTorque Bit Set, In Metal Storage Box** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable iTorque handle 7-26 in/lbs. 0.8-3.0 Nm, 50 insert bits & 1/4" bit holder.

Item	Slotted: 4.5, 5.5, 6.5, 8.0mm
No.	Phillips: #0, #1, #2, #3
28892	TORX®: T6, T7, T8, T9, T10, T15, T20, T25, T27, T3
lbs.	Hex Inch: 1/16, 5/64, 3/32, 7/64, 1/8, 2.57 9/64, 5/32, 3/16"
	Hex Metric: 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm
	Pozidriv: #0, #1, #2, #3
	Torq Set: #4, #5, #6, #8
	Square: #1, #2, #3
	Triwing: #0, #1, #2, #3, #4
	iTorque Handle Range 7 - 26 Inch/lbs. 28581 - 1/4" Bit Holder

With Certificate of Calibration



#### 52 Pc. Set

**28896 52 Piece iTorque Bit Set, In Metal Storage Box** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable iTorque handle 9-50 in/lbs. 1.0-6.0 Nm, 50 insert bits & 1/4" bit holder.

Item	Slotted: 4.5, 5.5, 6.5, 8.0mm
No.	Phillips: #0, #1, #2, #3
28896	TORX®: T6, T7, T8, T9, T10, T15, T20, T25, T27, T3
lbs.	Hex Inch: 1/16, 5/64, 3/32, 7/64, 1/8, 2.61 9/64, 5/32, 3/16"
	Hex Metric: 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm
	Pozidriv: #0, #1, #2, #3
	Torq Set: #4, #5, #6, #8
	Square: #1, #2, #3
	Triwing: #0, #1, #2, #3, #4
	iTorque Handle Range 9 - 45 Inch/lbs. 28581 - 1/4" Bit Holder



**Wiha SYSTEM 4 Micro Bits**



**750 SYSTEM 4 Slotted Bits** High alloy CVM steel, hardened, on 4 mm hex stock.

Item				
No.	mm	mm	Inch	lbs.
75008	0.8	28	1.1	.01
75012	1.2	28	1.1	.01
75015	1.5	28	1.1	.01
75018	1.8	28	1.1	.01
75020	2.0	28	1.1	.01
75025	2.5	28	1.1	.01
75030	3.0	28	1.1	.01
75035	3.5	28	1.1	.01
75040	4.0	28	1.1	.01



**751 SYSTEM 4 Phillips Bits** High alloy CVM steel, hardened, on 4 mm hex stock.

Item				
No.	Size	mm	Inch	lbs.
75105	000	28	1.1	.01
75110	00	28	1.1	.01
75115	0	28	1.1	.01
75120	1	28	1.1	.01



**753 SYSTEM 4 Hex Inch Bits** High alloy CVM steel, hardened, on 4 mm hex stock.

Item				
No.	Inch	mm	Inch	lbs.
75307	.028	28	1.1	.01
75309	.035	28	1.1	.01
75313	.050	28	1.1	.01
75350	1/16	28	1.1	.01
75352	5/64	28	1.1	.01
75354	3/32	28	1.1	.01
75356	7/64	28	1.1	.01
75358	1/8	28	1.1	.01
75360	9/64	28	1.1	.01
75340	5/32	28	1.1	.01



**757 SYSTEM 4 TORX® Bits** High alloy CVM steel, hardened, on 4 mm stock.

Item				
No.	Size	mm	Inch	lbs.
75701	T1	28	1.1	.01
75702	T2	28	1.1	.01
75703	T3	28	1.1	.01
75704	T4	28	1.1	.01
75705	T5	28	1.1	.01
75706	T6	28	1.1	.01
75707	T7	28	1.1	.01
75708	T8	28	1.1	.01
75709	T9	28	1.1	.01
75710	T10	28	1.1	.01
75715	T15	28	1.1	.01
75720	T20	28	1.1	.01



**757 SYSTEM 4 Security TORX® Bits** High alloy CVM steel, hardened, on 4 mm stock.

Item				
No.	Size	mm	Inch	lbs.
75735	T10s	28	1.1	.01
75742	T20s	28	1.1	.01



**753 SYSTEM 4 Hex Metric Bits** High alloy CVM steel, hardened, on 4 mm hex stock.

Item				
No.	mm	mm	Inch	lbs.
75307	0.7	28	1.1	.01
75309	0.9	28	1.1	.01
75313	1.3	28	1.1	.01
75315	1.5	28	1.1	.01
75320	2.0	28	1.1	.01
75325	2.5	28	1.1	.01
75330	3.0	28	1.1	.01
75340	4.0	28	1.1	.01



**753 SYSTEM 4 Metric Security Hex Bits** CVM steel, hardened, on 4 mm hex stock.

Item				
No.	mm	mm	Inch	lbs.
75322	2.0	28	1.1	.01
75327	2.5	28	1.1	.01
75332	3.0	28	1.1	.01
75342	4.0	28	1.1	.01

Item				
No.	Inch	mm	Inch	lbs.
75362	5/64	28	1.1	.01
75364	3/32	28	1.1	.01
75366	7/64	28	1.1	.01
75368	1/8	28	1.1	.01
75370	9/64	28	1.1	.01
75372	5/32	28	1.1	.01



**757 SYSTEM 4 Pentalobe Bits** High alloy CVM steel, hardened, on 4 mm stock.

Item				
No.	Size	mm	Inch	lbs.
75743	PL1	28	1.1	.01
75744	PL2	28	1.1	.01
75745	PL3	28	1.1	.01
75746	PL4	28	1.1	.01
75747	PL5	28	1.1	.01
75748	PL6	28	1.1	.01



**753 SYSTEM 4 Metric & Inch Nut Setters** CVM steel, hardened, on 4 mm hex stock.

Item No.				
Metric	mm	mm	Inch	lbs.
75820	2.0	30	1.2	.01
75821	2.5	30	1.2	.01
75822	3.0	30	1.2	.01
75823	3.5	30	1.2	.01
75824	4.0	30	1.2	.01
75825	4.5	30	1.2	.01
75826	5.0	30	1.2	.01
75827	5.5	30	1.2	.01

Inch	Inch	mm	Inch	lbs.
75810	5/64	30	1.2	.01
75811	3/32	30	1.2	.01
75812	7/64	30	1.2	.01
75813	1/8	30	1.2	.01
75814	9/64	30	1.2	.01
75815	5/32	30	1.2	.01
75816	3/16	30	1.2	.01
75817	7/32	30	1.2	.01

**1/4" Drive Micro Bit Tool Adapters**



**75802 Micro Bit To 1/4" Drive Insert Bit Adapter** uses magnets to hold 4mm Micro Bits

Item				
No.	Size	mm	mm	lbs.
75802	4.0	25	4.0	.01



**75803 Long Micro Bit To 1/4" Drive Insert Bit Adapter** uses spring clip non-magnetic to hold 4mm Micro Bits

Item				
No.	Size	mm	mm	lbs.
75803	4.0	38	4.0	.02

## Wiha Adjustable TorqueControl Tool Sets In Durable Storage Cases



53 Pc. Set

With Certificate of Calibration



59 Pc. Set

With Certificate of Calibration



59 Pc. Set

With Certificate of Calibration

**28595 53 Piece TorqueVario-S Bit Set, In Storage Box** Set includes ergonomic multi-component adjustable TorqueVario-S handle, 50 Insert bits, 1/4" Bit holder and Torque adjustment tool.

<b>Item</b>	<b>Slotted:</b> 4.5, 5.5, 6.5, 8.0mm
<b>No.</b>	<b>Phillips:</b> #0, #1, #2, #3
<b>28595</b>	<b>TORX®:</b> T6, T7, T8, T9, T10, T15, T20, T25, T27, T30
<b>lbs.</b>	<b>Hex Inch:</b> 1/16, 5/64, 3/32, 7/64, 2.04 1/8, 9/64, 5/32, 3/16"
	<b>Hex Metric:</b> 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm
	<b>Pozidriv®:</b> #0, #1, #2, #3
	<b>Torq Set:</b> #4, #5, #6, #8
	<b>Square:</b> #1, #2, #3
	<b>Tri-Wing:</b> #0, #1, #2, #3, #4
	28506 - Handle Range 10-50 In/lbs.
	28581 - 1/4" Bit Holder

**28589 59 Piece TorqueVario-S Bit Set, In Storage Box** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes 3 ergonomic multi-component adjustable TorqueVario-S handles, 39 Insert bits, 15 Sockets, 1/4" Bit holder, 1/4" Hex to 1/4" Square adapter and Torque adjustment tool.

<b>Item</b>	<b>Slotted:</b> 4.5, 5.5, 6.0mm
<b>No.</b>	<b>Phillips:</b> #0, #1, #2
<b>28589</b>	<b>TORX®:</b> T5, T6, T7, T8, T9, T10, T15, T20, T25, T30
<b>lbs.</b>	<b>Hex Inch:</b> .050, 1/16, 5/64, 3/32, 2.73 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4"
	<b>Hex Metric:</b> 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0mm
	<b>Pozidriv®:</b> #1, #2
	<b>Square:</b> #1, #2, #3
	<b>Inch Sockets:</b> 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 3/8"
	<b>Metric Sockets:</b> 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0mm
	<b>3 Handles:</b> 15 - 80 In/oz., 5 - 10 & 10 - 50 In/lbs.
	1/4" Bit Holder
	1/4" Hex to 1/4" Square adapter

**28689 59 Piece Torque Newton Meter Bit Set, In Storage Box** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes 3 ergonomic multi-component adjustable Torque Nm handles, 39 Insert bits, 15 Sockets, 1/4" Bit holder, 1/4" Hex to 1/4" Square adapter and Torque adjustment tool.

<b>Item</b>	<b>Slotted:</b> 4.5, 5.5, 6.0mm
<b>No.</b>	<b>Phillips:</b> #0, #1, #2
<b>28689</b>	<b>TORX®:</b> T5, T6, T7, T8, T9, T10, T15, T20, T25, T30
<b>lbs.</b>	<b>Hex Inch:</b> .050, 1/16, 5/64, 3/32, 2.73 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4"
	<b>Hex Metric:</b> 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0mm
	<b>Pozidriv®:</b> #1, #2
	<b>Square:</b> #1, #2, #3
	<b>Inch Sockets:</b> 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 3/8"
	<b>Metric Sockets:</b> 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0mm
	<b>3 Handles:</b> 0.1-0.6 Nm, 0.4-1.0 Nm & 1.0-5.0 Nm
	1/4" Bit Holder
	1/4" Hex to 1/4" Square adapter




**Wiha Adjustable TorqueControl Tool Sets In Durable Storage Box**



With Certificate of Calibration

**28590 24 Pc. TorqueVario-S Micro-Bit Set**

Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder & Torque adjustment tool. Packed in a compact durable storage box.


<b>Item</b>	<b>Slotted:</b> 1.5, 2.0, 3.0, 4.0mm
<b>No.</b>	<b>Phillips:</b> #00, #0, #1
<b>28590</b>	<b>TORX®:</b> T6, T7, T8, T9, T10, T15
	<b>Hex Inch:</b> .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32
lbs.	28404 - Handle Range 5 - 18 In/lbs.
1.35	



With Certificate of Calibration

**28593 24 Pc. TorqueVario-S Micro-Bit Set**


Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder & Torque adjustment tool. Packed in a compact durable storage box.

<b>Item</b>	<b>Slotted:</b> 1.5, 2.0, 3.0, 4.0mm
<b>No.</b>	<b>Phillips:</b> #00, #0, #1
<b>28593</b>	<b>TORX®:</b> T6, T7, T8, T9, T10, T15
	<b>Hex Inch:</b> .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32
lbs.	28501 - Handle Range 15-80 In/oz. (+/- 10%)
1.35	

**Wiha TorqueControl Sets In Durable Canvas Pouch**




**28596 8 Piece TorqueControl Set With Slotted & Phillips Blades** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 6 blades & Torque adjustment tool. Packed in a durable canvas pouch.

<b>Item No.</b>	<b>28596</b>
<b>Slotted:</b>	2.5, 3.0, 3.5, 4.0mm
	<b>Phillips:</b> #0, #1
lbs.	28404 - Handle Range 5 - 18 In/lbs.

With Certificate of Calibration



**28600 20 Piece TorqueControl Set With Slotted, Phillips, TORX®, Hex Inch Blades** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 18 blades & Torque adjustment tool. Packed in a durable canvas pouch.

<b>Item No.</b>	<b>28600</b>
<b>Slotted:</b>	2.5, 3.5, 4.0mm
<b>Phillips:</b>	#0, #1, #2
	<b>TORX®:</b> T7, T8, T9, T10, T15, T20
lbs.	<b>Hex:</b> 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
1.38	28506 - Handle Range 10 - 50 In/lbs.


With Certificate of Calibration



**28597 8 Pc. TorqueControl Set With TORX® Blades** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M

<b>Item</b>	<b>28597</b>
<b>No.</b>	<b>TORX®:</b> T7, T8, T9, T10, T15, T20
lbs.	28506 - Handle Range 10 - 50 In/lbs.

With Certificate of Calibration



**28598 8 Piece TorqueControl Set With TORXPlus® Blades** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M

<b>Item</b>	<b>TORXPlus®</b>	lbs.
<b>No.</b>	IP7, IP8, IP9, IP10, IP15, IP20	1.00
<b>28598</b>	28506 - Handle Range 10 - 50 In/lbs.	

With Certificate of Calibration



**28599 14 Piece TorqueControl Set With TORX® & TORXPlus® Blades** Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes Ergonomic multi-component adjustable TorqueVario-S handle, 12 blades & Torque adjustment tool. Packed in a durable canvas pouch.

<b>Item</b>	<b>TORXPlus®:</b>	lbs.
<b>No.</b>	IP7, IP8, IP9, IP10, IP15, IP20	1.25
<b>28599</b>	<b>TORX®:</b> T7, T8, T9, T10, T15, T20	
	28506 - Handle Range 10 - 50 In/lbs.	

With Certificate of Calibration









## Wiha Insulated TorqueControl Tools

Includes Certificate






**1000V**

**287 Insulated TorqueVario-S, With Window Scale Insulation**  **up to 1000Volt**  
EN ISO, BS EN, ASME, VDE, ASTM & NFPA70E standards, +/- 6% Accuracy. Handle sizes proportioned to optimize torque range. Audible and perceptible click when torque setting has been attained. (Requires Insulated Blade Holder #28350-Not Included)

Item No.	Range			
No.	Inch lbs.	Increments	mm	lbs. pkg.
28724	5 - 18	.5 In.lbs.	131	.43 1
28726	10 - 50	2 In.lbs.	138	.40 1
28727	18 - 62	2 In.lbs.	142	.69 1

Each TorqueVario handle has unique serial number and certificate of calibration

**287 Insulated TorqueVario-S Handle - In Newton Meter Scale** (Requires Insulated Blade Holder #28350-Not Included)

Item No.	Range			
No.	Nm	mm	lbs.	pkg.
28734	0.5 - 2.0	131	.45	1
28736	0.8 - 5.0	138	.45	1 (.2 Nm Increment)
28738	2.0 - 7.0	142	.72	1

## Wiha Insulated SlimLine Torque Blade Holder

**1000Volt**








**28350 Insulated SlimLine Torque Blade Holder** CVM steel. Through hardened black finish. ClicFix quick release holder securely locks blades.





Item No.	OAL	OAL			
No.	mm	mm	Inch	lbs.	pkg.
28350	6.0	170	6.75	.06	1

## Wiha Insulated SlimLine Blades





**283 Insulated Slotted SlimLine Blades**  
High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter than standard insulated tools.

Item No.			Slim	Max	Inch/			
No.	mm	Inch	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28307	2.5	.098	4.0	0.4	3.5	.02	1	
28308	3.0	.118	4.0	0.6	5.3	.02	1	
28310	3.5	.141	4.0	0.6	5.3	.02	1	
28309	4.0	.157	4.0	2.5	22.1	.02	1	
28312	5.5	.216	6.0	3.8	33.6	.02	1	
28315	6.5	.255	6.0	5.5	48.7	.02	1	





**283 Insulated Phillips SlimLine Blades**  
High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter than standard insulated tools.

Item No.		Slim	Max	Inch/			
No.	Size	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28317	1	4.0	3.8	33.6	.02	1	
28319	2	6.0	5.5	48.7	.02	1	





**283 Insulated Xeno Slotted Pozidriv® SlimLine Blades** Up to 33% narrower insulation dia. then standard insulated tools.

Item No.		Slim	Max	Inch/			
No.	Size	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28320	1	4.0	3.8	33.6	.02	1	
28321	2	6.0	5.5	48.7	.02	1	





**283 Insulated Xeno Slotted & Phillips SlimLine Blades** High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter than standard insulated tools.

Item No.		Slim	Max	Inch/			
No.	Size	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28327	1	4.0	3.8	33.7	.02	1	
28329	2	6.0	5.5	48.8	.02	1	





**283 Insulated Pozidriv® SlimLine Blades**  
SlimLine blades have up to 33% narrower insulation diameter than standard insulated tools.

Item No.		Slim	Max	Inch/			
No.	Size	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28330	1	4.0	3.8	33.7	.02	1	
28331	2	6.0	5.5	48.8	.02	1	





**283 Insulated Hex Metric SlimLine Blades**  
SlimLine blades have up to 33% narrower insulation dia. then standard insulated tools.

Item No.		Slim	Max	Inch/			
No.	Size	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28332	1.5	4.0	0.9	7.9	.02	1	
28333	2.0	4.0	1.8	15.9	.02	1	
28334	2.5	4.0	3.8	33.6	.02	1	
28335	3.0	4.0	5.5	48.7	.02	1	
28336	4.0	6.0	5.5	48.7	.02	1	
28337	5.0	6.0	5.5	48.7	.02	1	
28338	6.0	6.0	5.5	48.7	.02	1	

**283 Insulated TORX® SlimLine Blades**  
High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter than standard insulated tools.

Item No.		Slim	Max	Inch/			
No.	Size	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28339	T8	4.0	1.3	11.5	.02	1	
28344	T9	4.0	1.3	11.5	.02	1	
28340	T10	4.0	3.8	33.6	.02	1	
28341	T15	6.0	5.5	48.7	.02	1	
28342	T20	6.0	5.5	48.7	.02	1	
28343	T25	6.0	5.5	48.7	.02	1	

**283 Insulated Square SlimLine Blades**  
High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter than standard insulated tools.

Item No.		Slim	Max	Inch/			
No.	Size	Dia.	Nm	lbs.	lbs.	lbs.	pkg.
28346	1	4.0	3.8	33.6	.02	1	
28347	2	6.0	5.5	48.7	.02	1	

## Wiha Insulated Torque Ratchet Wrenches



1000Volt

### 301 Insulated Torque Ratchet

**Wrenches, 1/4, 3/8, 1/2" Drives Insulated to EN/IEC 60900:2004, ASTM F1505-10, CSA Standards** Visible reading scale for easy reading and adjustment. Locking endcap Torque adjuster for easy adjustment. Accuracy +/- 10%. Dual scale reading Ft. lbs. / Nm.

Item No.	OAL	OAL			
No.	Inch	mm	Inch	Nm	lbs.
30114	1/4"	210	8.25	5-25	1.02
30138	3/8"	370	14.5	5-50	2.72
30152	1/2"	530	21.0	40-220	3.64



1000Volt

### 30190 16 Pc. Inch Insulated 3/8" Drive Ratcheting Torque Wrench & Socket Set

CV steel, forged, oil-hardened sockets.

Item No.	3/8" Drive Sockets:
30190	1/4, 9/32, 5/16, 11/32, 3/8, 7/16
	1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8"
	3/8" x 125mm Extension Bar
8.80	3/8" x 250mm Extension Bar
	3/8" Drive Ratcheting Torque Wrench - 5-50 Nm

\*Sockets must be used with insulated ratchets & extensions



1000Volt

### 30192 16 Pc. Metric Insulated 3/8" Drive Ratcheting Torque Wrench & Socket Set

Item No.	3/8" Drive Sockets:
30192	8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20mm
	3/8" x 125mm Extension Bar
8.80	3/8" x 250mm Extension Bar
	3/8" Drive Ratcheting Torque Wrench - 5-50 Nm

\*Sockets must be used with insulated ratchets & extensions

## ESD Safe Adjustable TorqueControl Tools

With Certificate of Calibration



### 28591 24 Piece ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.	Slotted:	Phillips:	Hex Inch:
28591	1.5, 2.0, 3.0, 4.0mm	#00, #0, #1	.050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
1.57	28524 - Handle ESD Safe Range 5 - 10 Inch lbs.		



Includes Certificate

### 285 ESD Safe TorqueVario-S, With Window Scale EN ISO 6789, BS EN 26789, ASME B107.14M, +/- 6% Accuracy.

Ergonomic multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained. With Certificate of accuracy. Pkg. 1

Item No.	Range	Increments	mm	lbs.
28522*	15 - 80 (in/oz)	2.5 In.oz.	122-127	.33
28524	5 - 10	.2 In.lbs.	122-127	.34

Item No.	Range	Increments	mm	lbs.
28426	5 - 18	.5 In.lbs.	126-131	.46

Each TorqueVario handle has unique serial number and certificate of calibration

With Certificate of Calibration



### 28895 24 Piece ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.	Slotted:	Phillips:	Hex Metric:	Pentalobe:
28895	0.8, 1.2, 1.5, 2.0mm	#000, #00, #0	T1, T2, T3, T4, T5, T6	PL1, PL2, PL3, PL4
1.30	28500 - Handle ESD Safe .04 - .46Nm (+/-10%)			

With Certificate of Calibration



Packed in a compact durable storage box

+/- 10%

### 28890 24 Piece TorqueVario-S ESD Safe Micro-Bit Set

Certified to EN ISO 6789, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool.

Item No.	Slotted:	Phillips:	Hex Inch:
28890	1.5, 2.0, 3.0, 4.0mm	#00, #0, #1	.050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
1.35	28522 - ESD Safe Handle Range 15-80 Inch/oz.		

### ESD Safe TorqueControl Tools



Includes Certificate

#### 285 ESD Safe TorqueVario-S Newton

**Meter, With Window Scale** EN ISO 6789, BS EN 26789, ASME B107.14M, +/- 10% Accuracy. Ergonomic multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained. With Certificate of accuracy.

Item No.	Range				
No.	Nm	mm	Inch	lbs.	pkg.
28500	.04 - .46	124	4.875"	.35	1

ESD TorqueVario handle has unique serial number and certificate of calibration



#### 288 ESD Safe Pentalobe IPR Interchangeable Blades For TorqueVario-S Newton Meter

Handle tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, hard chromed.

Item No.	Size	mm	mm	lbs.	pkg.
28818	PL1	175	4.0	.07	1



#### 288 ESD Safe Slotted Interchangeable Blades For TorqueVario-S

Item No.	mm	Inch	mm	Nm	lbs.	pkg.
28805	3.0	.118	175	0.6	.07	1
28809	4.0	.157	175	2.5	.07	1



#### 288 ESD Safe TORX Interchangeable Blades For TorqueVario-S

Item No.	Size	mm	mm	Nm	lbs.	pkg.
28825	T5	175	4.0	0.4	.07	1
28827	T7	175	4.0	0.9	.07	1
28829	T9	175	4.0	2.5	.07	1



**28882 ESD Safe Bit Holder Adapter For 1/4" Drive Bits** Shaft CVM steel, hardened, corrosion protected. (Not for use in Insulated handles)

Item No.	Size	mm	mm	lbs.	pkg.
28882	1/4	162	4.0	.09	1

### T-handle TorqueControl Handles



Accuracy Ergonomic multi-component handle, light & compact

Includes Calibration Certificate

**289 TorqueFix T-handle** EN ISO 6789, BS EN 26789, ASME B107.14M, +/- 6%

Item No.	Torque In-lbs.	Torque Nm	mm x mm	lbs.	pkg.
28931	53.1	6	56 x 120	.81	1
28933	70.8	8	56 x 120	.82	1
28935	88.5	10	56 x 120	.79	1
28937	106.2	12	56 x 120	.79	1
28938	110.6	12.5	56 x 120	.80	1
28939	123.9	14	56 x 120	.80	1

Each TorqueFix T-handle has unique serial number and certificate of calibration



Includes Calibration Certificate

**28940 Adjustable TorqueVario STplus T-handle** EN ISO 6789, BS EN 26789, ASME B107.14M, +/- 6%

Item No.	Torque Nm	Torque In-lbs.	mm x mm	lbs.	pkg.
28940	5-14	44.3-123.9	56 x 120	.81	1

\* (1 Nm 8.8507) (Scale is shown in Nm only)

### T-handle TorqueControl Blades



#### 289 TORX Interchangeable Blades For TorqueFix T-Handle

**TORX** tip blades on 6mm Hex shafts. High alloy CVM steel, hardened, hard chromed.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
28903	T15	130	5.1	6.0	.10	1
28904	T20	130	5.1	6.0	.10	1
28905	T25	130	5.1	6.0	.11	1
28906	T27	130	5.1	6.0	.11	1
28907	T30	130	5.1	6.0	.11	1
28908	T40	130	5.1	6.0	.11	1



#### 289 TORXPlus Interchangeable Blades For TorqueFix T-Handle

**TORXPlus** tip blades on 6mm Hex shafts. High alloy CVM steel, hardened, hard chromed.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
28910	IP15	130	5.1	6.0	.10	1
28911	IP20	130	5.1	6.0	.10	1
28912	IP25	130	5.1	6.0	.11	1
28913	IP27	130	5.1	6.0	.11	1
28914	IP30	130	5.1	6.0	.11	1
28915	IP40	130	5.1	6.0	.11	1



#### 289 Hex Metric Interchangeable Blades For TorqueFix T-Handle

Hex tip blades on 6mm Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item No.	mm	mm	Inch	lbs.	pkg.
28916	3.0	130	5.1	.11	1
28917	4.0	130	5.1	.11	1
28918	5.0	130	5.1	.11	1
28919	6.0	130	5.1	.11	1



#### 289 Hex Inch Interchangeable Blades For TorqueFix T-Handle

Hex tip blades on 6mm Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item No.	Inch	mm	Inch	lbs.	pkg.
28920	1/8	130	5.1	.11	1
28921	9/64	130	5.1	.11	1
28923	3/16	130	5.1	.11	1
28924	7/32	130	5.1	.11	1

### Wiha T-handle TorqueControl Adapters



**289 TorqueFix Adapter For 1/4" & 3/8" Sockets** Shaft CVM steel, hardened, corrosion protected.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
28926	1/4	100	3.9	6.0	.12	1
28927	3/8	100	3.9	6.0	.15	1



**28925 TorqueFix Quick Release Bit Holder** Shaft CVM steel, hardened, corrosion protected.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
28925	1/4	125	4.9	6.0	.15	1

## Maximum Recommended Torque For Wiha Torque Blades

Tip Size	Style	Maximum Torque	
		Nm	in.lbs
T5	TORX	.4 Nm	3.5 in.lbs
T6	TORX	.6 Nm	5.31 in.lbs
T7	TORX	.9 Nm	7.9 in.lbs
T8	TORX	1.3 Nm	11.5 in.lbs
T9	TORX	2.5 Nm	22.1 in.lbs
T10	TORX	3.8 Nm	33.6 in.lbs
T15	TORX	5.5 Nm	48.7 in.lbs
T20	TORX	8.0 Nm	70.8 in.lbs
T25	TORX	8.0 Nm	70.8 in.lbs
IP5	TORX Plus	.5 Nm	4.4 in.lbs
IP6	TORX Plus	.8 Nm	7.0 in.lbs
IP7	TORX Plus	1.3 Nm	11.5 in.lbs
IP8	TORX Plus	2.0 Nm	17.7 in.lbs
IP9	TORX Plus	3.0 Nm	26.5 in.lbs
IP10	TORX Plus	4.5 Nm	39.8 in.lbs
IP15	TORX Plus	6.6 Nm	58.4 in.lbs
IP20	TORX Plus	8.0 Nm	70.8 in.lbs
IP25	TORX Plus	8.0 Nm	70.8 in.lbs
1.5	Slotted	.15 Nm	1.3 in.lbs
2.0	Slotted	.4 Nm	3.5 in.lbs
2.5	Slotted	.4 Nm	3.5 in.lbs
3.0	Slotted	.6 Nm	5.31 in.lbs
3.5	Slotted	1.1 Nm	9.7 in.lbs
4.0	Slotted	2.5 Nm	22.1 in.lbs
#000	Phillips	.4 Nm	3.5 in.lbs
#00	Phillips	.4 Nm	3.5 in.lbs
#0	Phillips	.9 Nm	7.9 in.lbs
#1	Phillips	3.8 Nm	33.6 in.lbs
#2	Phillips	5.5 Nm	48.6 in.lbs
1.5	Hex Metric	.9 Nm	7.9 in.lbs
2.0	Hex Metric	1.8 Nm	15.9 in.lbs
2.5	Hex Metric	3.8 Nm	33.6 in.lbs
3.0	Hex Metric	5.5 Nm	48.6 in.lbs
4.0	Hex Metric	8.0 Nm	70.8 in.lbs
.050	Hex Inch	.4 Nm	3.5 in.lbs
1/16	Hex Inch	.9 Nm	7.9 in.lbs
5/64	Hex Inch	1.8 Nm	15.9 in.lbs
3/32	Hex Inch	1.8 Nm	15.9 in.lbs
7/64	Hex Inch	3.8 Nm	33.6 in.lbs
1/8	Hex Inch	5.5 Nm	48.6 in.lbs
9/64	Hex Inch	8.0 Nm	70.8 in.lbs
5/32	Hex Inch	8.0 Nm	70.8 in.lbs





### Numerical Index by Item Number

Item No.	Page	Item No.	Page	Item No.	Page	Item No.	Page	Item No.	Page
28307	13	28365	4	28521	5	28568	6	28689	10
28308	13	28374	4	28522	14	28569	6	28724	13
28309	13	28375	4	28523	5	28571	6	28726	13
28310	13	28376	4	28524	14	28572	6	28727	13
28312	13	28377	4	28525	5	28573	6	28734	13
28315	13	28378	4	28527	6	28574	6	28736	13
28317	13	28379	4	28528	6	28575	6	28738	13
28319	13	28380	4	28529	6	28576	6	28740	12
28320	13	28381	4	28530	6	28577	6	28741	12
28321	13	28382	4	28531	6	28578	6	28742	12
28327	13	28383	4	28532	6	28579	6	28750	12
28329	13	28384	4	28533	6	28581	7	28751	12
28330	13	28385	4	28534	6	28582	7	28752	12
28331	13	28386	4	28535	6	28583	7	28791	12
28332	13	28387	4	28536	6	28587	6	28792	12
28333	13	28388	4	28537	6	28588	6	28795	12
28334	13	28389	4	28538	6	28589	10	28805	14
28335	13	28404	5	28539	6	28590	11	28809	14
28336	13	28408	5	28540	6	28591	14	28818	15
28337	13	28410	5	28541	6	28593	11	28825	14
28338	13	28411	5	28542	6	28595	10	28827	14
28339	13	28412	5	28543	6	28596	11	28828	14
28340	13	28413	5	28544	6	28597	11	28829	14
28341	13	28414	5	28545	6	28598	11	28882	6,15
28342	13	28415	5	28546	6	28599	11	28886	8
28343	13	28416	5	28547	6	28600	11	28887	8
28344	13	28417	5	28548	6	28611	6	28889	8
28346	13	28418	5	28549	6	28612	6	28890	14
28347	13	28419	5	28550	5	28613	6	28891	8
28349	4	28426	14	28551	5	28614	6	28892	8
28350	13	28500	15	28552	5	28616	6	28895	14
28351	4	28501	5	28553	5	28617	6	28896	8
28352	4	28502	5	28555	6	28618	6	28903	15
28353	4	28503	5	28556	6	28619	6	28904	15
28354	4	28505	5	28557	6	28620	7	28905	15
28355	4	28506	5	28558	6	28622	7	28906	15
28356	4	28507	5	28559	6	28624	7	28907	15
28357	4	28509	5	28560	6	28626	7	28908	15
28358	4	28511	5	28561	6	28627	7	28910	15
28359	4	28512	6	28562	6	28629	7	28911	15
28360	4	28513	5	28563	6	28632	7	28912	15
28361	4	28515	5	28564	6	28633	7	28913	15
28362	4	28517	5	28565	6	28637	7	28914	15
28363	4	28518	5	28566	6	28644	7	28915	15
28364	4	28519	5	28567	6	28655	5	28916	15



MANUFACTURING  
EXCELLENCE  
AWARD  
BESTES KMU  
2014

WIHA – WINNER OF THE  
MX AWARD 2014.  
GERMANY'S BEST SME.

**wiha**   
Tools that work for you

# PROFESSIONAL TORQUE CONTROL



(800) 494-6104  
fax: (800) 494-7456  
cservice@wihatools.com  
www.wihatools.com

Catalog Item No. 99001.wo  
version - 3/1/19

Subject to change  
without notice

©2019 Willi Hahn Corporation

®Torx is a registered trademark of  
Acument Intellectual Properties LLC.



## Wiha Quality Tools

1348 Dundas Circle  
Monticello, MN 55362  
tel: 763.295.6591  
fax: 763.295.6598

## Wiha Tools Canada Ltd.

www.wihatools.ca  
Brampton, ONT L6T 4X4  
tel: 866.494.0096 or 763.295.6591  
fax: 763.295.6598



To:



99977.wo - Pliers/Crimpers Catalog



99004.wo - Shop Tools Catalog



99914.wo - TORX Catalog



99951.wo - Bits Catalog



99919.wo - Insulated Catalog



99002.wo - Screwdrivers Catalog



99934.wo - Hex Tools Catalog



99006.wo - Tech Tools Catalog



99945.wo - ESD Catalog



99007.wo - Merchandise Catalog