

# Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, plain door, open bottom, 750x750x620mm, IP54, IK10

NSYPLAZ776G

## Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Enclosure type            | Multi-purpose  |
| Product or component type | Suitable enclosure   |
| Version                   | PLAZ   |
| Nominal height            | 750 mm   |
| Nominal width             | 750 mm   |
| Nominal depth             | 620 mm   |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 1 top part<br>1 bottom part<br>2 side part<br>1 rear panel<br>1 door<br>1 plinth |

## Complementary

|                             |   |
|-----------------------------|---|
| Body type                   | Sealed top and open bottom part assembled with side parts |
| Door type                   | Plain front   |
| Number of doors             | 1 door(s)   |
| Door opening side           | Reversible (120 °)  |
| Lock type                   | 2 points handle lock, 5 mm double-bar                     |
| Accessibility for operation | Rear<br>Bottom<br>Front                                   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element            |
| Material                    | Polyester reinforced with fibreglass                      |
| Colour                      | Grey (RAL 7035)   |
| Standards                   | IEC 62208   |
| Product certifications      | Veritas   |
| Electrical insulation class | Class II  |

## Environment

|                                     |  |
|-------------------------------------|--|
| IP degree of protection             | IP54 conforming to IEC 60529 (plinth type open bottom) |
| IK degree of protection             | IK10 conforming to IEC 62262 (plain door)              |
| Fire resistance                     | 960 °C conforming to IEC 62208                         |
| Ambient air temperature for storage | -35...90 °C  |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 81.5 cm |
| Package 1 Width              | 78.0 cm |
| Package 1 Length             | 65.0 cm |
| Package 1 Weight             | 31.0 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Recommended replacement(s)