

Characteristics

- Cutting of flat ribbon cable up to 81.5 mm (3.2 in.) width without conductor deformation
- Cutting anvil with fence for wire guidance is designed to provide a square cut
- Force multiplying mechanism for ease of use
- · Handles and blade holder made of high-strength steel for durability
- Cutting blade and anvil are replaceable
- Locking lever for protection and safety (closed blade)

Technical Data

- Dimensions: Length = 244 mm (9.6 in.), Width = 58 mm (2.3 in.)
- Weight: 360 g (0.8 lb.)

Important Notice

PRODUCT USE: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Warranty; Limited Remedy; Limited Liability.

3M's product warranty is stated in its Product Literature available upon request. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



3M Electronic Solutions Division Interconnect Products 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3M.com/interconnects

Please recycle. Printed in USA. © 3M 2008. All rights reserved. 80-6111-1970-1



3M[™] Round Conductor Flat Cable



3M[™] Color Coded Flat Cable



3M[™] Jacketed Flat Cable



3M[™] Twisted Pair Shielded Jacketed Flat Cable