



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

32.8 MHz LC Band Pass Filter

Part Number: AE32.8B5475



Electrical Specifications

Center Frequency: 32.8 MHz
0.5dB Passband: 31.8-34 MHz Min.
Insertion Loss @ 32.8 MHz: 8.0dB Max.
Return Loss: 14.0 dB Min.
Rejection1: 35dB Min @ 28.6 MHz
Rejection2: 35dB Min @ 37.4 MHz


Mechanical

Connector Type: PC-Mount
Dimensions: 1.5" X 0.5" x 0.4".

Environmental

Operating Temperature: -25°C to +70°C
Storage Temperature: -40°C to +90°C
Shock: 10 G. 11ms
Vibration: 10 G. 5 to 200Hz

Outline Drawing:



Tolerance: +/-0.01 inches [+/-0.3mm] Angles: +/-1 Deg.

*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.


*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.

70 Outwater Lane Phone: (973) 772-4242
Garfield, NJ 07026 Fax : (973) 321-3941

Email: sales@anatechelectronics.com
Web: www.anatechelectronics.com



Simulation Plot:



Note: This is a simulated response plot. Actual performance might differ.