



210  
170±15  
10-15  
250  
SEAL  
PE-LD  
MADE IN CHINA

**Electrical test:**

- 100% short, open, miss wire test
- Conduct resistance: 2 ohm(max)
- Insulation resistance: 5 Mohm(min)
- Dielectric test: DC 300V/10ms

NO.	NAME	Q'TY	SPECIFICATION
⑧	TUBE	2	HEAT SHRINK TUBE BLACK OD1.5*L15MM
⑦	PE BAG	1/5	CLEAR SIZE:330*380*0.05mm PRINT BLACK*MADE IN CHINA**5PCS*
⑥	PE FILM	1	PE FILM CLEAR W35*L3000mm.
⑤	PE BAG	1	CLEAR SIZE:210*250*0.05mm PRINT BLACK*MADE IN CHINA*
④	SCREW	4	SCREW:#4-40UNC L47mm,NICKEL PLATED,INSULATION COLOR BEIGE(IV-29)
③	OUT JACKET	43.5g	BEIGE(IV-29) 40P PVC(MOULD NO:WM-113)
	IN JACKET	8g	CLEAR LDPE(MOULD NO:NM-049)
②	CONN	2	DB 9PIN FEMALE PIN G/F SHELL-NICKEL SOLDER TYPE INSULATION COLOR BLUE
①	CABLE	1	NOUL 30AWG(7/0.10)*9C+D.W+AL/MY+JACKET COROL:BEIGE(IV-29) OD:5.0mm. L5000±20mm.

PIN ASSIGNMENT	
P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
SHELL	SHELL

**RoHS compliant**  
Unit: mm

Scale	Free				Date	Name	Customer-No.
TOLERANCE				Drawn	20.02.2017	Amy	ASSMANN WSW-No. <b>AK153-5</b>
				Approved	04.09.2017	Fred	
DIM	TOL	①	Delete the wire color for pin assignment	04.09.2017	Fred	Drawing-No.	
		②	Drawn	20.02.2017	Amy	<b>ASS 7882 CA</b> rev01	
Angle	TOL	Id.	Modification	Date	Name		

