

### Feature

- § Low Power Consumption
- § High Intensity
- § I.C. compatible


### Applications

- § Commercial Outdoor Sign Board
- § Front Panel Indicator
- § Dot-Matrix Module
- § LED Bulb

### Description

- § These High Intensity LEDs are Based on AlGaAs/GaAs Material Technology
- § Emitted color:Red
- § Water Transparent Lens

### Package Dimension



\*Tolerance :  $\pm \frac{0.01}{0.25}$       Unit :  $\pm \frac{\text{inch}}{\text{mm}}$

### Absolute Maximum Ratings at Ta=25°C

Symbol	Parameter	Max.	Unit
PD	Power Dissipation	100	mW
VR	Reverse Voltage	5	V
IAF	Average Forward Current	25	mA
IPF	Peak Forward Current (Duty=0.1, 1kHz)	85	mA
—	Derating Linear Form 25°C	0.4	mA/°C
Topr	Operating Temperature Range	-40 to + 80	°C
Tstg	Storage Temperature Range	-40 to + 100	°C
Lead Soldering Temperature [1.6mm (0.063inch) From Body] 260°C For 5 Seconds.			

### Electrical / Optical Characteristics and Curves at Ta=25°C

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
VF	Forward Voltage	IF= 20 mA		1.8	2.1	V
IR	Reverse Current	VR= 5 V			100	$\mu$ A
$\Delta \theta$	Half Intensity Angle	IF= 20 mA		30		Deg.
IV	Luminous Intensity	IF= 20 mA		480		mcd.
$\lambda_p$	Peak Wavelength	IF= 20 mA		655		nm
$\lambda_d$	Dominant Wavelength	IF= 20 mA		640		nm

## Electrical Characteristics at Ta=25°C

Symbol	I <sub>V</sub>	V <sub>F</sub>		$\lambda_D$	
Parameter	Luminous Intensity	Forward Voltage		Dominant Wavelength	
Condition	IF=20mA		IF=20mA		IF=20mA
Unit	mcd		V		nm
Binning	Grade	Range	Grade	Range	Grade
	BIN 14	480~680	B	1.8~1.9	R1
			C	1.9~2.0	R2
			D	2.0~2.1	

Intensity: Tolerance of minimum and maximum =  $\pm 15\%$


Vf: Tolerance of minimum and maximum =  $\pm 0.05\text{v}$

NOTE:

1. Static electricity and surge damages the LED. It is recommend to use a anti-static wrist band or anti-electrostatic glove when handing the LEDs. All devices, equipment and machinery must be properly grounded.
2. Specific binning requirements –please contact our home office

## Radiation Diagram

IF=20 mA 50% Power Angle Angle =30°



## RED

### Typical Electro-optical Characteristic Curves (25°C Free Air Temperature Unless Otherwise Specified)

Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength

