



Buck chopper MOSFET Power Module

V_{DSS} = 500V
R_{DSon} = 38mΩ typ @ T_j = 25°C
I_D = 90A @ T_c = 25°C



Application

- AC and DC motor control
- Switched Mode Power Supplies

Features

- Power MOS 7® MOSFETs
 - Low R_{DSon}
 - Low input and Miller capacitance
 - Low gate charge
 - Avalanche energy rated
 - Very rugged
- Kelvin source for easy drive
- Very low stray inductance
 - Symmetrical design
 - Lead frames for power connections
- Internal thermistor for temperature monitoring
- High level of integration

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- RoHS Compliant

Absolute maximum ratings

Symbol	Parameter	Max ratings	Unit
V _{DSS}	Drain - Source Breakdown Voltage	500	V
I _D	Continuous Drain Current	T _c = 25°C	A
		T _c = 80°C	
I _{DM}	Pulsed Drain current	360	
V _{GS}	Gate - Source Voltage	±30	V
R _{DSon}	Drain - Source ON Resistance	45	mΩ
P _D	Maximum Power Dissipation	T _c = 25°C	W
I _{AR}	Avalanche current (repetitive and non repetitive)	46	A
E _{AR}	Repetitive Avalanche Energy	50	mJ
E _{AS}	Single Pulse Avalanche Energy	2500	

 **CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

Electrical Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
I_{DSS}	Zero Gate Voltage Drain Current	$V_{GS} = 0\text{V}$, $V_{DS} = 500\text{V}$	$T_j = 25^\circ\text{C}$			200	μA
		$V_{GS} = 0\text{V}$, $V_{DS} = 400\text{V}$	$T_j = 125^\circ\text{C}$			1000	
$R_{DS(on)}$	Drain – Source on Resistance	$V_{GS} = 10\text{V}$, $I_D = 45\text{A}$			38	45	$\text{m}\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}$, $I_D = 5\text{mA}$		3		5	V
I_{GSS}	Gate – Source Leakage Current	$V_{GS} = \pm 30\text{ V}$, $V_{DS} = 0\text{V}$				± 150	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
C_{iss}	Input Capacitance	$V_{GS} = 0\text{V}$ $V_{DS} = 25\text{V}$ $f = 1\text{MHz}$			11.2		nF
C_{oss}	Output Capacitance				2.4		
C_{rss}	Reverse Transfer Capacitance				0.18		
Q_g	Total gate Charge	$V_{GS} = 10\text{V}$ $V_{Bus} = 250\text{V}$ $I_D = 90\text{A}$			246		nC
Q_{gs}	Gate – Source Charge				66		
Q_{gd}	Gate – Drain Charge				130		
$T_{d(on)}$	Turn-on Delay Time		Inductive switching @ 125°C		18		ns
T_r	Rise Time	$V_{GS} = 15\text{V}$			35		
$T_{d(off)}$	Turn-off Delay Time	$V_{Bus} = 333\text{V}$			87		
T_f	Fall Time	$I_D = 90\text{A}$			77		
E_{on}	Turn-on Switching Energy	Inductive switching @ 25°C $V_{GS} = 15\text{V}$, $V_{Bus} = 333\text{V}$ $I_D = 90\text{A}$, $R_G = 2\Omega$			1510		μJ
E_{off}	Turn-off Switching Energy				1452		
E_{on}	Turn-on Switching Energy		Inductive switching @ 125°C		2482		μJ
E_{off}	Turn-off Switching Energy	$V_{GS} = 15\text{V}$, $V_{Bus} = 333\text{V}$ $I_D = 90\text{A}$, $R_G = 2\Omega$			1692		

Chopper diode ratings and characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit	
V_{RRM}	Maximum Peak Repetitive Reverse Voltage	$V_R = 600\text{V}$		600			V	
I_{RM}	Maximum Reverse Leakage Current		$T_j = 25^\circ\text{C}$			250	μA	
I_F	DC Forward Current		$T_c = 70^\circ\text{C}$		60		A	
V_F	Diode Forward Voltage	$I_F = 60\text{ A}$			1.6	1.8	V	
		$I_F = 120\text{ A}$			1.9			
		$I_F = 60\text{ A}$	$T_j = 125^\circ\text{C}$		1.4			
t_{rr}	Reverse Recovery Time	$I_F = 60\text{ A}$ $V_R = 400\text{V}$ $di/dt = 200\text{A}/\mu\text{s}$	$T_j = 25^\circ\text{C}$		130		ns	
			$T_j = 125^\circ\text{C}$		170			
Q_{rr}	Reverse Recovery Charge		$T_j = 25^\circ\text{C}$		220		nC	
			$T_j = 125^\circ\text{C}$		920			



Thermal and package characteristics

Symbol	Characteristic		Min	Typ	Max	Unit
R_{thJC}	Junction to Case Thermal Resistance	Transistor			0.18	°C/W
		Diode			0.9	
V_{ISOL}	RMS Isolation Voltage, any terminal to case t = 1 min, $I_{isol} < 1\text{mA}$, 50/60Hz		2500			V
T_J	Operating junction temperature range		-40		150	°C
T_{STG}	Storage Temperature Range		-40		125	
T_C	Operating Case Temperature		-40		100	
Torque	Mounting torque	To Heatsink	M5	2.5	4.7	N.m
Wt	Package Weight				160	g


Temperature sensor NTC (see application note APT0406 on www.microsemi.com for more information).

Symbol	Characteristic		Min	Typ	Max	Unit
R_{25}	Resistance @ 25°C			50		kΩ
$B_{25/85}$	$T_{25} = 298.15\text{ K}$			3952		K

$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]} \quad T: \text{Thermistor temperature}$$






R_T : Thermistor value at T







SP4 Package outline (dimensions in mm)









ALL DIMENSIONS MARKED "*" ARE TOLERENCED AS : $\boxed{\phi/\emptyset 1}$

See application note APT0501 - Mounting Instructions for SP4 Power Modules on www.microsemi.com

Typical Performance Curve






Microsemi reserves the right to change, without notice, the specifications and information contained herein

Microsemi's products are covered by one or more of U.S patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. U.S and Foreign patents pending. All Rights Reserved.