

Screwdriver - SZK PH3 VDE - 1212536

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Screwdriver, PH crosshead, VDE insulated, size: PH 3 x 150 mm, 2-component grip, with non-slip grip

The figure shows the SZK PH2 version

Product Features

- VDE approval
- Screwdrivers for Phillips screws with Pozidriv and Phillips Recess screw head



Key commercial data

Packing unit	1 1
Weight per Piece (excluding packing)	160.0 GRM
Custom tariff number	82054000
Country of origin	Czech Republic

Technical data

Dimensions

Length (b)	262 mm
Width (a)	40 mm
Blade height	150 mm

General

Design	Phillips
Type	Straight
Material	Alloyed tool steel
Test standard	DIN/ISO 8764-1 PH IEC 60900:2004

Screwdriver - SZK PH3 VDE - 1212536

Classifications

eCl@ss

eCl@ss 4.0	21040401
eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040401
eCl@ss 6.0	21040401
eCl@ss 7.0	21040409
eCl@ss 8.0	21040409

ETIM

ETIM 4.0	EC000144
ETIM 5.0	EC000144

UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

Approvals

Approvals


Approvals

VDE Zeichengenehmigung / GOST / GOST

Ex Approvals

Approvals submitted

Approval details

VDE Zeichengenehmigung 

Screwdriver - SZK PH3 VDE - 1212536

Approvals

GOST 

GOST 

Drawings

Pictogram

