


TAIYO-HK1005-V1

Taiyo Yuden 0402 High Frequency Inductor Kit

Part No.	Inductance	Maximum Rated Current (mA) (-55 ~ +125°C)	Maximum DC Resistance (Ω)	Sample Qty.
HK10051N0S-T	1.0nH +/-0.3nH	300mA	0.08 Ω	50
HK10051N2S-T	1.2nH +/-0.3nH	300mA	0.09 Ω	50
HK10051N5S-T	1.5nH +/-0.3nH	300mA	0.10 Ω	50
HK10051N8S-T	1.8nH +/-0.3nH	300mA	0.12 Ω	50
HK10052N2S-T	2.2nH +/-0.3nH	300mA	0.13 Ω	50
HK10052N7S-T	2.7nH +/-0.3nH	300mA	0.13 Ω	50
HK10053N3S-T	3.3nH +/-0.3nH	300mA	0.16 Ω	50
HK10053N9S-T	3.9nH +/-0.3nH	300mA	0.21 Ω	50
HK10054N7S-T	4.7nH +/-0.3nH	300mA	0.21 Ω	50
HK10055N6S-T	5.6nH +/-0.3nH	300mA	0.23 Ω	50
HK10056N8J-T	6.8nH +/-5%	300mA	0.25 Ω	50
HK10058N2J-T	8.2nH +/-5%	300mA	0.28 Ω	50
HK100510NJ-T	10nH +/-5%	300mA	0.31 Ω	50
HK100512NJ-T	12nH +/-5%	300mA	0.40 Ω	50
HK100515NJ-T	15nH +/-5%	300mA	0.46 Ω	50
HK100518NJ-T	18nH +/-5%	300mA	0.55 Ω	50
HK100522NJ-T	22nH +/-5%	300mA	0.60 Ω	50
HK100527NJ-T	27nH +/-5%	300mA	0.70 Ω	50
HK100533NJ-T	33nH +/-5%	200mA	0.80 Ω	50
HK100539NJ-T	39nH +/-5%	200mA	0.90 Ω	50
HK100547NJ-T	47nH +/-5%	200mA	1.00 Ω	50
HK100556NJ-T	56nH +/-5%	200mA	1.00 Ω	50
HK100568NJ-T	68nH +/-5%	180mA	1.20 Ω	50
HK100582NJ-T	82nH +/-5%	150mA	1.30 Ω	50
HK1005R10J-T	100nH +/-5%	150mA	1.50 Ω	50
HK1005R12J-T	120nH +/-5%	150mA	1.60 Ω	50

* All components in this kit are RoHS compliant. Specifications subject to change without notice. Components in this kit are for design trial and testing performance and are not intended for use in mass production.

Physical Dimensions	
L	1 ± 0.05 (0.039 ± 0.002)
W	0.5 ± 0.05 (0.02 ± 0.002)
T	0.5 ± 0.05 (0.02 ± 0.002)
e	0.25 ± 0.1 (0.01 ± 0.004)
Unit: mm (inches)	



TAIYO YUDEN

Taiyo Yuden (USA), Inc.
www.t-yuden.com