

Data sheet | Item number: 883-2442

Jumper; 2-way; insulated; yellow

www.wago.com/883-2442



Color:

Data

Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Ratings per IEC/EN

Nominal voltage (III/3)	1000 V
Rated current	380 A

Physical data

Width	66.3 mm / 2.61 inches
-------	-----------------------

Material Data

Note (material data)	Information on material specifications can be found here
Color	yellow
Insulation material	Polyamide (PA66)
Flammability class per UL94	V2
Weight	204.6 g

Commercial data

ETIM 8.0	EC000489
ETIM 7.0	EC000489
PU (SPU)	5 pcs
Packaging type	bag
Country of origin	DE
GTIN	4055143940566
Customs tariff number	85366990990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Bid Text

883-2404	xml	Download
docx - Datei	2.8 kB	
883-2442	docx	Download

Subject to changes. Please also observe the further product documentation!



X81 - Datei

12.6 kB

Additional Information

pdf
2.3 MB

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 883-2442


[URL](#)

[Download](#)

Jumper; 2-way; insulated; yellow

Installation Notes

Commoning



Commoning

Step 1: Insert the 2- or 3-way jumper into the conductor entry to connect adjacent terminal blocks.



Commoning

Step 2: Mount the yellow insulating cap and snap it to the housing to position the jumper in the clamping unit.

Subject to changes. Please also observe the further product documentation!



Commoning

Step 3: By tightening the screw in the actuation slot, the jumper is secured in the conductor entry. If required, a conductor can also be inserted into the conductor entry and clamped together with the jumper.

A multiple potential distribution is possible due to the conductor entry on both sides. The jumpers are designed for the rated current of the screw terminal block.

Subject to changes. Please also observe the further product documentation!