

**Technical specification :**

Rated voltage: IEC 61076-2-104	30 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Coupling screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

**Installation specification:**



Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

**Contact assignment:**

- 1 ■ brown
- 2 ■ white
- 3 ■ blue
- 4 ■ black

Part no:	Description:	Length L:	Cable:
42-10108	SAL - 8 - RSU4 - 2 / K1	2m	TPU, UL 20549, black, 4x0,25mm <sup>2</sup> Cable: 781-K12400
42-10109	SAL - 8 - RSU4 - 3 / K1	3m	
42-10110	SAL - 8 - RSU4 - 5 / K1	5m	
42-10111	SAL - 8 - RSU4 - 10 / K1	10m	
42-xxxxx	SAL - 8 - RSU4 - ... / K1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND	Directive 2002/95/EC RoHS compliant	Index: a 17.03.2011 VF Ä3945 Coupling screw modified, spanner flats added, data sheet modified	 dim. in mm	title: <b>Male connector M8x1 axial screw/ snap</b>									
		tolerance of cable: L < 4m: L + 40mm L > 4m: L + 1%			<table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>09.10.07</td> <td>Franz</td> </tr> <tr> <td>appd.</td> <td>09.10.07</td> <td>Mankopf</td> </tr> </table>		date	name	drawn	09.10.07	Franz	appd.	09.10.07
			date		name								
		drawn	09.10.07		Franz								
appd.	09.10.07	Mankopf											
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		dwg no: <b>42K1A023</b>											
		part no: <b>see table</b>											