TE Internal #: 6-1734774-7

PCI & PCI Express Connectors, Cable-to-Board, 36 Position, .039 in [1 mm] Centerline, Vertical, Black, Height .394 in [10 mm], Width .

346 in [8.8 mm]

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > PCI & PCI Express Connectors











Connector System: Cable-to-Board

Number of Positions: 36

PCI Generation: 2

Centerline (Pitch): 1 mm [ .039 in ]

Termination Post & Tail Length: 3.1 mm [ .122 in ]

PCB Contact Termination Area Plating Material Thickness

### **Features**

#### **Product Type Features**

Product Type Features	
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of PCB Mount Retention Features	2
Number of Positions	36
PCB Mount Orientation	Vertical
Ejector	Without
Electrical Characteristics	
Operating Voltage	50 VAC
Body Features	
Product Weight	2.55 g[.09 oz]
Primary Product Color	Black
Contact Features	

2.54 μm



Contact Mating Area Plating Material	Gold
PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
	30 μin
Contact Current Rating (Max)	1.1 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Termination Post & Tail Length	3.1 mm[.122 in]
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	PA 46
Centerline (Pitch)	1 mm[.039 in]
Dimensions	
Dimensions  Connector Length	25 mm[.984 in]
	25 mm[.984 in] 1.57 mm[.062 in]
Connector Length	
Connector Length PCB Thickness (Accepted)	1.57 mm[.062 in]
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)	1.57 mm[.062 in] 2.4 mm[.094 in]
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)  Connector Height	1.57 mm[.062 in] 2.4 mm[.094 in] 10 mm[.394 in]
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)  Connector Height  Connector Width	1.57 mm[.062 in] 2.4 mm[.094 in] 10 mm[.394 in]
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)  Connector Height  Connector Width  Usage Conditions	1.57 mm[.062 in] 2.4 mm[.094 in] 10 mm[.394 in] 8.8 mm[.346 in]
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)  Connector Height  Connector Width  Usage Conditions  Operating Temperature Range	1.57 mm[.062 in] 2.4 mm[.094 in] 10 mm[.394 in] 8.8 mm[.346 in]
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)  Connector Height  Connector Width  Usage Conditions  Operating Temperature Range  Industry Standards	1.57 mm[.062 in] 2.4 mm[.094 in] 10 mm[.394 in] 8.8 mm[.346 in]  -40 – 85 °C[-40 – 185 °F]
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)  Connector Height  Connector Width  Usage Conditions  Operating Temperature Range  Industry Standards  Bus Type	1.57 mm[.062 in]  2.4 mm[.094 in]  10 mm[.394 in]  8.8 mm[.346 in]  -40 – 85 °C[-40 – 185 °F]  PCI Express
Connector Length  PCB Thickness (Accepted)  PCB Thickness (Recommended)  Connector Height  Connector Width  Usage Conditions  Operating Temperature Range  Industry Standards  Bus Type  PCI Generation	1.57 mm[.062 in]  2.4 mm[.094 in]  10 mm[.394 in]  8.8 mm[.346 in]  -40 – 85 °C[-40 – 185 °F]  PCI Express

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------



EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





# Customers Also Bought





















### **Documents**

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_6-1734774-7\_F.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6-1734774-7\_F.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_6-1734774-7\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Product Specification** 

English

**Product Specification** 

English

**Product Environmental Compliance** 

**TE Material Declaration** 

English