## FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 180908-1

Crimp Terminal Housings, Tab, Tab Housing, 2 Position, Straight, Red, Polyamide, Contact Mating Retention, Mating Alignment,


FASTIN-FASTON 250


View on TE.com >



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings











Terminal Type: Tab

Connector & Housing Type: Tab Housing

Number of Positions: 2
Terminal Orientation: Straight
Primary Product Color: Red

### **Features**

### **Product Type Features**

Froduct Type reatures	
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Tab Housing
Configuration Features	
Number of Positions	2
Body Features	
Primary Product Color	Red
Contact Features	
Terminal Type	Tab
Terminal Orientation	Straight
Contact Mating Retention	With
Mechanical Attachment	

With

Mating Alignment



Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

#### **Housing Features**

Housing Material	Polyamide
Centerline (Pitch)	7.4 mm[.291 in]

#### **Dimensions**

Product Length	31.5 mm[1.24 in]

### **Usage Conditions**

Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
	•

### **Packaging Features**

Packaging Quantity	3000
Packaging Method	Carton

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Compatible Parts













## Also in the Series | FASTIN-FASTON 250







Insertion & Extraction Tools(2)



PCB Terminals(2)



Quick Disconnects(254)

# Customers Also Bought













### **Documents**

## **Product Drawings**

FF 250 TAB HSG 2P NYLON RED

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_180908-1\_AB.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_180908-1\_AB.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_180908-1\_AB.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

White Paper: Nylon Discoloration

English

## **Product Specifications**

**Application Specification** 

English

## **Agency Approvals**

**UL Report** 

English