



specifications

CRI	Voltage	Ambient Temp (F)	Color Temp	Material	IP Rating	Efficacy	Gross Weight	Beam Angle	Warranty	Case QTY
80	100-277 V ⚡	-40° - 140°	5000K	copper free aluminum housing	IP 66	140 LM / W	19.84 lbs	120°	6 years	2 pcs

select your fixture


Part Number	Color Temp	Consumption	Lumen Output	Emergency Driver	Dimensions
GI-EPH-C250-C1D2	5000K	60W	8,400	No	47" x 4.7" x 9.5"
GI-EPH-C250-EMC1D2	5000K	60W	8,400	Yes	47" x 4.7" x 9.5"

add your accessories*

Accessories Part Number	Description
1.) GI-ACC-EPUB	U-Bracket
2.) GI-ACC-PC	Pendant Chain



1.)



2.)

optional*



large

compact



Features

- Rated for high temperatures, humidity, dust and vapor locations
- Built for a variety of purposes such as spot light, tunnel light, and general illumination in hazardous locations
- Light weight design
- Heavy duty and high impact resistance
- Various installation options for particular applications
- Non-dimmable

Distribution Diagram

Center Beam fc	Beam Width	
4ft	683fc	11ft
8ft	170fc	21ft
12ft	73fc	32ft
16ft	39fc	43ft
20ft	26fc	53ft

■ Vert, Spread; 120°
■ Horiz, Spread; 120°

Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.

