

TECHNICAL DATA SHEET

Part#: 7275E

Cutters - 50° Angulated Head - Blade Length .16" - Short Handle
Offers excellent visibility and accessibility with our smallest angulated (.16") blade

The 7275E Lazer Line® miniature angulated/tapered optimum flush cutter with a cutting capacity of .003" - .025" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. This 4.75" tool has a 40° angled tips and a set-screw to prevent overtravel while prolonging the life of the tool. It features an ergonomically molded antimicrobial Anti-Static grip (10¹⁰ ohms/sq surface resistivity) with dual leaf springs.

- Precision Level ★★★★★
- Material Carbon
- Surface Resistivity 10¹⁰ ohms/sq
- Shape Angulated Head
- Type of Cut Optimum Flush
- Cutting Capacity .001 - .018"
- Blade Angle 50°
- Blade Length .16" (4mm)
- Body Width 0.42" (10.5mm)
- Body Height 4.75" (118.75mm)
- OAL 3
- Weight (OZ) 662847009679
- UPC 8203.20.60.60
- Schedule B EAR99
- ECCN 27111511
- UNSPSC Code USA
- Country of Origin Angled Head
- Group

