Powerful, portable, and designed with the technician in mind

Features:

- Analog Testing for up to 8MP cameras
- 16M color, backlit 4" TFT display
- Designed to facilitate the installation and maintenance of surveillance video equipment using Standard Definition analog NTSC/PAL, HD-TVI, HD-CVI, and AHD camera systems
- Supports more than 30 Pan-Tilt-Zoom (PTZ) protocols using RS485 port
- · Automatically identifies type of coding
- 12VDC/1A output
- Video Recording, Screen Shot & Frame-by-Frame or Streaming Playback
- Generate Analog NTSC/PAL and HD Video (up to 1080P 30fps) Test Patterns
- Monitor the data flow between the analog camera and the DVR system
- · Check microphone/audio on the camera
- · Built-in, super-bright Flashlight
- Rechargeable, long-lasting Lithium Polymer Battery
- Includes camera tester, BNC, RS485, USB, audio, power, and 12V power output cables, battery, belt clip, and tool bag with shoulder strap
- 1 year warranty





Ordering Information:

8065 CamView HD Pro Ruggedized HD Camera Tester



850 Perimeter Road • Manchester, NH • (603) 669-6400 • info@triplett.com

lin

CE

Powerful, portable, and designed with the technician in mind

Specifications

-	
Analog and HD Video T	esting
Video Format	Auto recognizes NTSC/PAL, HD-CVI 3.0, HD-TVI 3.0, AHD 2.0
Test Pattern	Generates NTSC/PAL, HD-CVI, HD-TVI, or AHD test patterns (720P/1080P)
Signal Level	1vpp
Input/Output	Video IN BNC, Video OUT BNC
Digital Zoom	Supports 8-level portion view
Capture	Take snap shot or record video
Power Output	
Output	12V/1A power output to camera. Connector is 4mm diameter; pin is 1.6mm diameter
System	
Screen	4.0 inch TFT 800*RGB*480(WVGA) resolution, 16.7M color, backlight with adjustable brightness
Operation	Power key, 13 control keys
Language	User selectable English, French, Spanish, Russian, Chinese
Auto Shut-off	Disable / 5~60 minutes
Software	Supports online upgrade through USB using a Windows computer
Power	
Charger	12V/1A (5.5mm) power supply
Battery	Dedicated battery, user replaceable, 7.4V lithium-ion polymer battery, capacity 10.4Wh
Battery runtime	Approximately 5 hours
Power Saving	Auto power off; Real-time battery level indicator
Other	
Storage	8GB flash built in; use micro USB port to connect external device
LED Light	(2) 35lm LED lights
Dimensions	6.9 x 4.4 x 1.5" (175 x 113 x 37mm)
Weight	3.5lbs (1.6kg)



