



CODICE	MATERIALE	FINITURA
P/N	MATERIAL	PLATING
94536-0100	OTTONE	GREGGIO / PLAIN
94536-0101	BRASS	STAGNATO / TIN PLATED

SEZ. DI AGGRAFFAGGIO : 0.5 ↔ 1.5 mm²
 Ø ISOLANTE : 2.0 ↔ 3.6 mm

WIRE RANGE : 0.5 ↔ 1.5 mm²
 Ø INSULATION : 2.0 ↔ 3.6 mm

IMBALLO: IN BOBINE CON CARTA INTERMEDIA,
 Nr. 3 BOBINE PER SCATOLA

PACKAGING: ON REELS WITH INTERLEAVING PAPER,
 Nr. 3 REELS PER BOX

S.P.Q. : 9000 pz.

S.P.Q. : 9000 pcs.

Std. Descr. : FEM TERM 4.8/0.8 RA BRS UNPL 0.5-1.5

Std. Descr. : FEM TERM 4.8/0.8 RA BRS TIN 0.5-1.5

ADD MATERIAL NBR. EC NO: Z2005-0074 DRWNL: SANTESS 2004/11/18 CHKDR: SANDANO 2004/11/18 APPR: GZUIN 2004/11/19 B1	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	FIRST ANGLE PROJECTION		
		mm	INCH	DRAWN BY LSANTESS	DATE 1996/09/18	TITLE FLAG FEMALE TERMINAL FOR 4.8 X 0.8 TABS				
		4 PLACES ± ---	± ---	CHECKED BY	DATE	MOLEX INCORPORATED				
		3 PLACES ± ---	± ---	APPROVED BY MPREVIAT	DATE 1996/09/18					
		2 PLACES ± 0.10	± ---	ANGULAR ± 2 °		MATERIAL NO.	DOCUMENT NO. SD-94536-002	SHEET NO. 1 OF 1		
1 PLACE ± 0.2	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					