



#### General ordering data

Order No.	9507770000
Part designation	NexT 62/45/16 2gp 7032
Version	Ex enclosure, 160 mm, 620 mm, 450 mm, Sheet steel 2.02 mm (14 SWG)
EAN	4008190480356
Qty.	1 pc(s).

#### Dimensions

Fixing dimension, height	450 mm
Fixing dimension, width	506 mm
Height	160 mm
Length	620 mm
Width	450 mm

#### General details

Cover fixing	Removable cover + M6 screws
Enclosure fixing	Outside mounting with 10 mm holes
Integral fixing	4 x 10 mm spacers
Sealing material	Chloroprene (cover & flange)
Version cover	closed
Colour	RAL 7032 - pebble grey
Surface finish	RAL 7032, textured
Class of protection to EN 60529	IP 66
Weight	17,000 g
Ambient temperature, min.	-40 °C
Ambient temperature, max.	85 °C

#### Screwed cable glands top/bottom

M 12	74
M 16	48
M 20	26
M 25	20
M 32	8
M 40	6

#### Screwed cable glands top/bottom

M 50	5
Side of enclosure	Top / Bottom

#### Screwed cable glands, left/right

M12	74
M16	48
M20	26
M25	20
M32	8
M40	6
M50	5
On housing side	left / right

#### Approvals

Approvals institutes



#### Classifications

ETIM 2.0	EC000049
ETIM 3.0	EC000049
eClass 4.1	27-14-12-06
eClass 5.0	27-18-05-02
eClass 5.1	27-18-05-02

#### Similar products

Order No.	Part designation	Version
9523620000	NexT 62/45/16 0gp 7032	Ex enclosure, 160 mm, 620 mm, 450 mm, Sheet steel 2.02 mm (14 SWG)
9523480000	NexT 62/45/16 0gp ss	Ex enclosure, 160 mm, 620 mm, 450 mm, Stainless steel 1.4404
9522920000	NexT 62/45/16 1gp 7032	Ex enclosure, 160 mm, 620 mm, 450 mm, Sheet steel 2.02 mm (14 SWG)
9522640000	NexT 62/45/16 1gp ss	Ex enclosure, 160 mm, 620 mm, 450 mm, Stainless steel 1.4404
9508580000	NexT 62/45/16 2gp ss	Ex enclosure, 160 mm, 620 mm, 450 mm, Stainless steel 1.4404
9523060000	NexT 62/45/16 3gp 7032	Ex enclosure, 160 mm, 620 mm, 450 mm, Sheet steel 2.02 mm (14 SWG)
9522780000	NexT 62/45/16 3gp ss	Ex enclosure, 160 mm, 620 mm, 450 mm, Stainless steel 1.4404
9507840000	NexT 62/45/16 4gp 7032	Ex enclosure, 160 mm, 620 mm, 450 mm, Sheet steel 2.02 mm (14 SWG)
9508650000	NexT 62/45/16 4gp ss	Ex enclosure, 160 mm, 620 mm, 450 mm, Stainless steel 1.4404