



- Notes
- 1 Applicable metal clamper: SR30-P(CL103-0266-5-00)
 - 2 The recommended clamp torque of ref.No. ⑤ : 1.5~2N · m.
 - 3 The recommended clamp torque of ref.No. ⑥ : 0.1~0.15N · m.
 - 4 Apply Loctite 243, HENKEL JAPAN or equivalent to the threaded portion of ref.No. ① and ② In order to prevent loosening.
 - 5 Rotation examples of ref. No. ① and ② are shown.
 - 6 Applicable tools
 Clamping tool for SR30-P : SR30-10PM-T(CI150-0054-4-00)
 Soldering and fastening tool:SR30-10P-T0A(CI150-0004-6-00)
 - 7 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure, please confirm before the use. Also, please confirm the workability in advance, as it may be tight when passing the cable through the part No. ⑥ bushing.

5	Brass	Nickel plating	9	Steel	Chromate treatment (Equivalent chrom um)	JIS # 3117 M2.5X0.45X3		
3	Polyacetal	(White)	8	Brass	Chrome plating			
2	Brass	Surface plating : Gold plating 0.24μ min. Under plating : Nickel plating 3.24μ min.	7	Brass	Chrome plating			
1	Zinc alloy	Nickel plating	6	Chloroprene rubber	(Black)			
NO.	MATERIAL	FINISH .	REMARKS	NO.	MATERIAL	FINISH .	REMARKS	
UNITS	mm	SCALE	2 : 1	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE

APPROVED	: TP. KOMATSU	202211201	DRAWING NO.	EDC-020857-32-00
CHECKED	: HY. KOBAYASHI	20221201	PART NO.	SR30-10PX-6P(32)
DESIGNED	: HY. KISHI	20221201	CODE NO.	CL0103-0336-9-32
DRAWN	: KR. SUZUKI	20221129		