



GO

Advanced



United



Global Home



Products

About Us

Products

Product highlights

Product overview

Cable Ties and Fixings (1668)

Insulation Products (2244)

Cable Protection Systems (1683)

Installation Devices (197)

Identification Systems (2438)

Wire and Cable Markers (1776)

Control Panel Labelling (68)

Industrial Identification (310)

Security Labeling (156)

Hazardous Area Identification (85)

Printers and Software (43)

Application Tooling (134)

Connectivity (1207)

T.I.P.S.

Project Management-Autotool-
Automatic Cable Tying Systems

Competences

Career

News & Events

Downloads

TAGH90



Article number: 557-00034

These labels are particularly suitable for permanent identification on flat surfaces for production equipment or IT devices. Using unique numbering, graphics, or barcodes the labels give excellent asset identification possibilities. The extensive range has sizes to suit most needs.

In nearly all ares, especially for cable and wire identification in computer and electronic business. For problem-free printing, we recommend our TagPrint Pro (Page 245 CHECK PAGE!!!).



Print

Application Method		Each roll of labels is loaded onto a reusable spindle. Simply drop the label roll into the printer, pull the labels over the top (like loading film into a camera) and close the cover. No need to mechanically feed and align the labels.
Colour		Silver matt (SR)
Mounting method Identification ETIM		Pasting / Stick
Type		TAGH90-799
Variant		Roller form
With label space ETIM		Yes
Height (H)		12.7 mm
Height (H) (imperial)		0.5 "
Length (L)		12.7 mm
Length (L) (imperial)		0.5 "
Print Method		Thermal Transfer
Width (W)		38.1 mm
Width (W) (imperial)		1.5 "
Width of Liner (WL)		41.27 mm
Width of LIner (WL) (imperial)		1.625 "
Carton Quantity		1
EAN code		4031026230443
Pack Cont.		500
Pack Cont.		500
Quantity per		roll

UPC	089306225867
Weight	0.3 kg
▼	
Adhesive	Acrylic
Adhesive Operating Temperature	-40 °C to +150 °C
Curing Temperature	from +10 °C
Material	799
Material	Type 799, Polyester, silver matt (SR)
Operating Temperature	-40 °C to +150 °C
Shortcut Adhesive	Acryl
Specification	UL -Recognised
UL OCD link	Link Link
UL-File Number	MH18396
▼	
UNSPSC Key	39131504