



NOTES:

1. Electrical Specifications:

- Meets USB 2.0 specifications
- Low level Contact Resistance: 30 mOhm max.
- Insulation Resistance 1000 MOhm min.
- Currant Rating: 1.5 A max. @ 25°C
- DWV: 500 VAC/60s at sea level
- Operating Temperature: -40°C to +80°C

2. Material and Finish:

- M28 Thread Coupling Ring: Polyester (Black); UL94 V-0
- Plug Housing: Polyester (Black); UL94 V-0
- Interfacial Seal: Silicone, Color: White
- Cable Gland: PA (Black); UL94 V-0
- Cable Gland Seal: NBR, Color: Black
- USB Insulator: PBT, UL 94V-0, Color: White
- USB Overmold: PVC, UL94 V-0, Color: Black
- USB Metal Shell: SPCC. Nickel plated
- USB Contact: Copper Alloy, 30 u" min. Au over 40 u" min. Nickel Plated

3. Shielded USB Cable Configuration

AWM 2725 AWG28/1p + AWG24/2c, OD: 4.5 mm Color: black

4. RoHS compliant

Directive 2002/95/EC
"RoHS"
Compliant

Cable Length L	Part Number
2 m	17-200481
3 m	17-200491
4.5 m	17-200501

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION	Customer:		Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in m	
	Name		Title	Approval Date		Autodesk Inventor	Material: See Notes	
			2009		Date	Name	Title:	
			Draw.	Jul. 08	Vincent Ke	USB Patch Cord		
		Appd.	Jul. 08	J. chaudry	USB 2.0 Type A Plug (Strain Relief)			
		Norm				to USB 2.0 Type B Plug (Standrad)		
		D-old				Drawing No.: 17K1A130		
a original				CONEC		Part No.: SEE P/N ABOVE		
Rev.	Changes	Date	Name			DIN A3		
						Sheet 1/1		