

# 3M™ Polishing Films

## 951M • 958M • 961M • 968M

### Product Description

3M™ Polishing Films 951M, 958M, 961M and 968M are comprised of resilient fibers coated onto a polyester film backing, this non-abrasive product is usually used as a carrier for a polishing compound or slurry and is available in sheets, discs, and rolls.

### Applications

- Glass polishing, plastic finishing, metal finishing, wafer edge cleaning, roll superfinishing and fiber optic cleaning.

### Key Features

- Durable carrier for compounds or slurries
- Fiber structure can provide unique results
- Soft texture, but ability to cut through work piece substrate
- Keeps compound at interface of work piece

### Product I.D. Mineral Size Grading Chart

Product ID (plain back)	Product ID (PSA back)	Mineral	Color
951M	958M	None	White
961M	968M	None	Purple

### Converted Forms

- Sheets, Discs and Rolls.
- Maximum width 22".

### Backing

- Flocked fibers on 3 mil polyester film.

### Storage and Shelf Life

Recommended Storage Conditions:

Temperature: 50-90°F (10-32°C)

Relative humidity: 30-70%

(There is no degradation with time. It is recommended that product be used within 24 months of purchase.)



## Regulatory

For regulatory information about this product, refer to our website at [3M.com](http://3M.com).

## For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-251-8634. Address correspondence to: 3M, Electronics Markets Materials Division, 3M Center, Building 225-3S-06, St. Paul, MN 55144-1000. Our fax number is 651-778-4244 or 1-877-369-2923. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

## Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

## Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

## Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

## Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



### Electronics Markets Materials Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
1-800-251-8634 phone  
651-778-4244 fax  
[www.3M.com/electronics](http://www.3M.com/electronics)

3M is a trademark of 3M Company.  
Please recycle. Printed in U.S.A.  
©3M 2013. All rights reserved.  
60-5002-0079-9

