



# Ball screw linear actuator ELGC-BS-KF-60-200-12P

Part number: 8061492

FESTO



## Data sheet

| Feature  | Value  |
|--|--|
| Working stroke                                     | 200 mm   |
| Size   | 60   |
| Stroke reserve                                     | 0 mm   |
| Reversing backlash                                 | 150 µm   |
| Screw diameter                                     | 12 mm  |
| Spindle pitch                                      | 12 mm/U  |
| Mounting position                                  | Any  |
| Guide  | Recirculating ball bearing guide   |
| Structural design                                  | Electromechanical linear axis with ball screw  |
| Motor type   | Stepper motor<br>Servo motor   |
| Spindle type                                       | Ball screw drive   |
| Symbol   | 00991211   |
| Position sensing                                   | For proximity sensor<br>For inductive proximity sensors  |
| Max. acceleration                                  | 15 m/s <sup>2</sup>  |
| Max. rotational speed                              | 4000 1/min   |
| Max. speed   | 0.8 m/s  |
| Repetition accuracy                                | ±0.01 mm   |
| Duty cycle   | 100%   |
| LABS (PWIS) conformity                             | VDMA24364 zone III   |
| Suitability for the production of Li-ion batteries | Metals with more than 1% copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Cleanroom class                                    | Class 7 according to ISO 14644-1   |
| Degree of protection                               | IP40   |
| Ambient temperature                                | 0 °C ... 50 °C   |
| Impact energy in the end positions                 | 0.001 J  |
| Hinweis zur Aufprallenergie in den Endlagen        | At maximum speed of the reference run of 0.01 m/s  |
| 2nd moment of area Iy                              | 441000 mm <sup>4</sup>   |
| 2nd moment of area Iz                              | 542000 mm <sup>4</sup>   |
| No-load torque at maximum travel speed             | 0.246 Nm   |
| No-load torque at minimum travel speed             | 0.042 Nm   |
| Max. force Fy                                      | 600 N  |
| Max. force Fz                                      | 1800 N   |

| Feature  | Value                                |
|--|--------------------------------------|
| Fy for the guidance calculation at a service life of 5000 km or 5 million cycles | 3641 N                               |
| Fz for the guidance calculation at a service life of 5000 km or 5 million cycles | 3641 N                               |
| Fy with theoretical service life of 100 km (from a guide perspective only)       | 13400 N                              |
| Fz with theoretical service life of 100 km (from a guide perspective only)       | 13400 N                              |
| Max. torque Mx   | 29.1 Nm                              |
| Max. torque My   | 31.8 Nm                              |
| Max. torque Mz   | 31.8 Nm                              |
| Mx for the guidance calculation at a service life of 5000 km or 5 million cycles | 29.1 Nm                              |
| My for the guide calculation at a service life of 5000 km or 5 million cycles    | 31.8 Nm                              |
| Mz for the guidance calculation at a service life of 5000 km or 5 million cycles | 31.8 Nm                              |
| Mx with theoretical service life of 100 km (from a guide perspective only)       | 107 Nm                               |
| My with theoretical service life of 100 km (from a guide perspective only)       | 117 Nm                               |
| Mz with theoretical service life of 100 km (from a guide perspective only)       | 117 Nm                               |
| Distance between slide surface and guide center                                  | 54.6 mm                              |
| Max. radial force on actuator shaft  | 230 N                                |
| Max. feed force Fx   | 200 N                                |
| Torsion moment of inertia It   | 29800 mm <sup>4</sup>                |
| Mass moment of inertia JH per meter of stroke                                    | 0.10779 kgcm <sup>2</sup>            |
| Mass moment of inertia JL per kg of payload                                      | 0.036476 kgcm <sup>2</sup>           |
| Mass moment of inertia JO  | 0.02235 kgcm <sup>2</sup>            |
| Feed constant  | 12 mm/U                              |
| Maintenance interval   | Life-time lubrication                |
| Moving mass  | 525 g                                |
| Additional weight per 10 mm stroke   | 51 g                                 |
| Dynamic deflection (load moved)  | 0.05% of axis length, maximum 0.5 mm |
| Static deflection (load at standstill)   | 0.1 % of axis length                 |
| Interface code, actuator   | T42                                  |
| Material of end caps   | Die cast aluminum, painted           |
| Profile material   | Wrought aluminum alloy, anodized     |
| Note on materials  | RoHS-compliant                       |
| Cover strip material   | High-alloy stainless steel           |
| Drive cover material   | Die cast aluminum, painted           |
| Slide carriage material  | Steel                                |
| Guide rail material  | Steel                                |
| Slide material   | Die-cast aluminum                    |
| Spindle nut material   | Steel                                |
| Spindle material   | Steel                                |