



DATE	DESCRIPTION	REV.
6.27.19	CHANGE AS PER ECN 19-060 ROTATE TEST PINT IN THE POCKET FOR 90°	A
7.29.19	CHANGE AS PER ECN 19-062 INSULATION MAT'L WAS PA6T	B

**NOTES:**

1. SUPPLIED ON TAPE AND REEL ONLY.

**TAPE AND REEL SPECIFICATIONS:**

2. TAPE:  
MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER  
ANSI/EIA-481 STANDARD
3. REEL:  
7" [180.0] DIA. 1000 PIECES PER REEL

**TEST POINT SPECIFICATIONS:**

1. CONTACT:  
MAT'L -.008 [0.20] TH'K PHOSPHOR BRONZE  
FINISH: SILVER PLATE
2. INSULATOR:  
MAT'L -LCP, UL 94V-0  
(SEE COLOR IN THE TABLE)

PART NO.	BASE COLOR	PART NO.	BASE COLOR
5190TR	RED	5195TR	BROWN
5191TR	BLACK	5196TR	GREEN
5192TR	WHITE	5197TR	BLUE
5193TR	ORANGE	5198TR	GREY
5194TR	YELLOW	5199TR	PURPLE

**KEYSTONE ELECTRONICS CORP.**  
www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

PART NAME: TEST POINT

MATERIAL: AS NOTED

FINISH <b>AS NOTED</b>	DRN BY NT	DATE 2.26.19
	APPD RH	SCALE 5X

TOLERANCES INCH [MM]  
DECIMAL ±.005 [±0.13]  
ANGULAR ± 1°  
UNLESS OTHERWISE SPECIFIED

CODE: C

DWG NO.  
**5190TR-5199TR**

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.