

## Tripp Lite series 72V Extended Battery Module (EBM) for 2200VA and 3000VA SmartPro UPS Systems, 2U Rack/Tower

MODEL NUMBER: BP72VRM2U



External battery pack provides extended runtime for compatible UPS systems in small business, education, retail, financial or healthcare applications.

### Features

#### Backup Battery Module Gives Your Compatible Eaton UPS System Extended Runtime

The BP72VRM2U offers extended battery runtime when used in conjunction with 2200VA and 3000VA SmartPro® UPS systems. It can also be daisy-chained for a maximum of four matching battery packs to deliver even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for safe, simple installation.

#### Supports 2U Rack or Tower Installation

This backup battery pack's multi-use form factor supports mounting in 2U of space in EIA-standard 19-inch open frame racks or enclosures using the included 4-post rail kit and mounting brackets. Tower stands are also included for optional upright configuration.

### Highlights

- Connects to select expandable UPS systems for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Includes heavy-gauge cabling with high-current 72V DC connectors
- Supports 2U rack mounting or upright tower installation using included accessories

### System Requirements

Compatible only with SMART2200RMXL2U, SMART2200RMXLN, SMART3000RMXL2U, SMART3000RMXLN, SMX3000XLRT2UA, and SMX3000XLRT2UN SmartPro UPS systems

### Package Includes

- BP72VRM2U External 72V Battery Pack
- External battery cable
- Rack-mounting hardware
- Tower support stands
- Quick Start Guide

## Specifications

OVERVIEW	
UPC Code	037332279101
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
DC System Voltage (VDC)	72

Internal UPS Replacement Battery Cartridge	&nbsp;  <a class="productLink" href="//tripplite.eaton.com/replacement-battery-for-eaton-9px-ups-and-ebm~744-A3121">744-A3121</a>&nbsp;  </td>
Battery Replacement Description	Hot-swappable, user-replaceable batteries. EBM requires 2 Replacement Battery Cartridges.
<b>PHYSICAL</b>	
Rack Height	2U
External Battery Pack Form Factor	Rack/Tower
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount; Tower
Minimum Required Rack Depth (cm)	68.58
Minimum Required Rack Depth (inches)	27
Unit Dimensions (hwd / in.)	3.400 x 17.200 x 23.700
Unit Weight (lbs.)	89.1
Unit Weight (kg)	40.42
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CAN/CSA C22.2; cTUVus; cUL Listed
Product Compliance	CE (Europe); RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (U.S. & Canada)	2-year limited warranty