

**Features**

- Optimized Body Diode Reverse Recovery Performance
- Low On-resistance and Low Conduction Losses
- Ultra Low Gate Charge Cause Lower Driving Requirement
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free. "Green" Device (Note 1)
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

**Maximum Ratings**


- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 0.83°C/W Junction to Case

Parameter	Symbol	Rating	Unit	
Drain-Source Voltage	$V_{DS}$	650	V	
Gate-Source Voltage	$V_{GS}$	±30	V	
Continuous Drain Current	$I_D$	$T_C=25^\circ C$	20	A
		$T_C=100^\circ C$	12	A
Pulsed Drain Current (Note 2)	$I_{DM}$	60	A	
Single Pulse Avalanche Energy (Note 3)	$E_{AS}$	484	mJ	
Repetitive Avalanche Energy	$E_{AR}$	0.7	mJ	
Avalanche Current	$I_{AR}$	3.5	A	
Total Power Dissipation	$P_D$	151	W	


Note:

1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <100ppm antimony compounds.
2. Repetitive Rating; Pulse Width Limited by Maximum Junction Temperature.
3.  $I_{AS}=3.5A$ ,  $V_{DD}=50V$ ,  $R_G=25\Omega$ , Starting  $T_J=25^\circ C$ .

**Internal Structure and Marking Code**




1. Gate
2. Drain
3. Source



YWWTT: 5 codes in total  
Y is the year  
WW is the cycle  
TT is the line type

**N-CHANNEL  
Super-Junction  
Power MOSFET**

**TO-220AB(H)**



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.172	0.188	4.37	4.77	
B	0.049	0.057	1.25	1.45	
C	0.246	0.270	6.25	6.85	
D	0.594	0.634	15.10	16.10	
E	0.382	0.406	9.70	10.30	
F	0.346	0.370	8.80	9.40	
G	0.102	0.118	2.60	3.00	
H	0.087	0.102	2.20	2.60	
J	-----	0.134	-----	3.40	
K	0.046	0.058	1.17	1.47	
L	0.028	0.037	0.70	0.95	
M	0.200		5.08		TYP.
N	0.100		2.54		TYP.
O	0.502	0.543	12.75	13.80	
P	0.134	0.150	3.40	3.80	Φ
Q	0.016	0.026	0.40	0.65	
R	0.276	-----	7.00	-----	
S	0.217	-----	5.50	-----	

**Electrical Characteristics @ 25°C (Unless Otherwise Specified)**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
<b>Static Characteristics</b>							
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	650			V	
Gate-Source Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 30V$			$\pm 100$	nA	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=650V, V_{GS}=0V, T_C=25^\circ C$			1	$\mu A$	
		$V_{DS}=650V, V_{GS}=0V, T_C=125^\circ C$			100		
Gate-Threshold Voltage <sup>(Note 4)</sup>	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.5		4.5	V	
Drain-Source On-Resistance <sup>(Note 4)</sup>	$R_{DS(on)}$	$V_{GS}=10V, I_D=10A$		150	170	m $\Omega$	
Gate Resistance <sup>(Note 4)</sup>	$R_G$	f = 1.0MHz Open Drain		12		$\Omega$	
<b>Dynamic Characteristics <sup>(Note 5)</sup></b>							
Input Capacitance	$C_{iss}$	$V_{DS}=100V, V_{GS}=0V, f=1MHz$		1724		$\mu F$	
Output Capacitance	$C_{oss}$			61			
Reverse Transfer Capacitance	$C_{rss}$			6			
Total Gate Charge	$Q_g$	$V_{DS}=520V, V_{GS}=10V, I_D=20A$		39		nC	
Gate-Source Charge	$Q_{gs}$			8			
Gate-Drain Charge	$Q_{gd}$			15			
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=400V, I_D=20A$ $V_{GS}=10V, R_{GEN}=25\Omega$		15		ns	
Turn-On Rise Time	$t_r$			59			
Turn-Off Delay Time	$t_{d(off)}$			121			
Turn-Off Fall Time	$t_f$			44			
<b>Drain-Source Diode Characteristics</b>							
Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V, I_S=20A$			1.2	V	
Continuous Body Diode Current	$I_S$				20	A	
Reverse Recovery Time	$t_{rr}$	$V_R=400V, I_F=I_S,$ $di_F/dt = 100A/\mu s$		423		ns	
Reverse Recovery Charge	$Q_{rr}$				5.3		$\mu C$
Peak Reverse Recovery Current	$I_{rrm}$				25		A

Note:

4. Pulse Test: Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 1\%$ .

5. Guaranteed by Design, not Subject to Production.

**Curve Characteristics**

Fig. 1 - Typical Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 -  $R_{DS(ON)} - I_D$




Fig. 4 - Capacitance Characteristics




Fig. 5 - Total Gate Charge Characteristics





Fig. 6 - Normalized On Resistance Characteristics



## Ordering Information

Device	Packing
Part Number-BP	Bulk:50pcs/Tube, 1Kpcs/Box,5Kpcs/Carton

**\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp.* products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.