

Components of electronic housing - UM-BASIC/PRO 122 COVER-R KMGY - 2202046

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Lateral element (right) with mounting foot for DIN rails for UM-BASIC profiles with a PCB width of 122 mm

Product Features

- Item is from the UM-BASIC/UM-PRO product range
- PVC press-drawn section (UM-BASIC) or PA (UM-PRO)
- Available in individual lengths
- Available in the overall widths of 72 mm, 108 mm, and 122 mm
- Variety of connection technologies
- Can be mounted on the DIN rail

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	20.0 g
Custom tariff number	39269097
Country of origin	Poland

Technical data

General

Housing type	Panel mounting base
Housing material	Polyamide
Color	light gray

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

Dimensions

Length	15.5 mm
Constructional height	40 mm
Width	142.3 mm

Technical data

Flammability rating according to UL 94	V0
--	----

Components of electronic housing - UM-BASIC/PRO 122 COVER-R KMGY - 2202046

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27400501

ETIM

ETIM 5.0	EC002779
----------	----------