



**ESD Safe Adjustable TorqueControl Tools**



Includes Certificate



**285 ESD Safe TorqueVario-S, With Window Scale**

EN ISO 6798, BS EN 26789, ASME B107.14M, +/- 6% Accuracy  
Ergonomic multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible and perceptible click when torque setting has been attained. With Certificate of accuracy.

| Item    | Range           | ↔           |           | ↔    |      | ↔ |
|---------|-----------------|-------------|-----------|------|------|---|
| No.     | Inch lbs.       | Increments  | mm        | lbs. | pkg. |   |
| 285 22* | 15 - 80 (in/oz) | 2.5 Inch oz | 122 - 127 | .33  | 1    |   |
| 285 24  | 5 - 10          | .2 Inch lbs | 122 - 127 | .34  | 1    |   |
| 285 26  | 7.5 - 20        | .5 Inch lbs | 126 - 131 | .42  | 1    |   |

\* +/- 10% (This unit only)

Each TorqueVario handle has unique serial number and certificate of calibration



With Certificate of Calibration



**285 91 Set 24 Pcs. ESD Safe Adjustable TorqueVario-S Bit Set**

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

| Item No. | ↔  |
|----------|--|
| 285 91   | Slotted: 1.5, 2.0, 3.0, 4.0mm lbs.                       |
|          | Phillips: #00, #0, #1 1.31                               |
|          | TORX®: T6, T7, T8, T9, T10, T15                          |
|          | Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32" |
|          | 28524 Handle ESD Safe Range 5 - 10 Inch lbs.             |

**285 92 Set 24 Pcs. ESD Safe Adjustable TorqueVario-S Bit Set**

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

| Item No. | ↔  |
|----------|--|
| 285 92   | Slotted: 1.5, 2.0, 3.0, 4.0mm lbs.                       |
|          | Phillips: #00, #0, #1 1.31                               |
|          | TORX®: T6, T7, T8, T9, T10, T15                          |
|          | Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32" |
|          | 28526 Handle ESD Safe Range 7.5 - 20 Inch lbs.           |

See ESD Safe Tools  
On Pages 127-139, 163-165



**288 ESD Safe Slotted Interchangeable Blades For TorqueVario-S**

Slotted tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

| Item   | ⊖   | ⊖    | ↔   | ↔    | Max. Torque | ↔    | SHOP |
|--------|-----|------|-----|------|-------------|------|------|
| No.    | mm  | Inch | mm  | lbs. | Nm          | pkg. |      |
| 288 01 | 1.5 | .059 | 175 | .07  | 0.15        | 1    |      |
| 288 03 | 2.0 | .078 | 175 | .07  | 0.4         | 1    |      |
| 288 05 | 3.0 | .118 | 175 | .07  | 0.6         | 1    |      |
| 288 07 | 3.5 | .139 | 175 | .07  | 1.1         | 1    |      |
| 288 09 | 4.0 | .157 | 175 | .07  | 2.5         | 1    |      |



**288 ESD Safe Phillips Interchangeable Blades For TorqueVario-S**

Phillips tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, satin hard chrome finish.

| Item   | ⊕    | ↔   | ⬡   | ↔    | Max. Torque | ↔    | SHOP |
|--------|------|-----|-----|------|-------------|------|------|
| No.    | Size | mm  | mm  | lbs. | Nm          | pkg. |      |
| 288 10 | 000  | 175 | 4.0 | .07  | 0.4         | 1    |      |
| 288 12 | 00   | 175 | 4.0 | .07  | 0.4         | 1    |      |
| 288 14 | 0    | 175 | 4.0 | .07  | 0.9         | 1    |      |
| 288 16 | 1    | 175 | 4.0 | .07  | 3.8         | 1    |      |



**288 ESD Safe TORX® Interchangeable Blades For TorqueVario-S**

TORX® tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, hard chromed.

| Item   | ⊗    | ↔   | ⬡   | ↔    | Max. Torque | ↔    | SHOP |
|--------|------|-----|-----|------|-------------|------|------|
| No.    | Size | mm  | mm  | lbs. | Nm          | pkg. |      |
| 288 25 | T5   | 175 | 4.0 | .07  | 0.4         | 1    |      |
| 288 26 | T6   | 175 | 4.0 | .07  | 0.6         | 1    |      |
| 288 27 | T7   | 175 | 4.0 | .07  | 0.9         | 1    |      |
| 288 28 | T8   | 175 | 4.0 | .07  | 1.3         | 1    |      |
| 288 29 | T9   | 175 | 4.0 | .07  | 2.5         | 1    |      |
| 288 30 | T10  | 175 | 4.0 | .07  | 3.8         | 1    |      |



With Certificate of Calibration +/- 10%



**288 90 Set 24 Piece TorqueVario-S ESD Safe Micro-Bit Set**

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool. Packed in a compact durable storage box.

| Item No. | ↔  |
|----------|--|
| 288 90   | Slotted: 1.5, 2.0, 3.0, 4.0mm Phillips: #00, #0, #1 lbs. |
|          | TORX®: T6, T7, T8, T9, T10, T15 1.33                     |
|          | Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32" |
|          | 28522 ESD Safe Handle Range 15-80 Inch/oz.               |