

# Product data sheet

Specifications



## Limit switch, 9007, 240 VAC 10amp ms +options

9007MS05S0300

### Main

Range of product	9007
Series name	Miniature potted
Product or component type	Limit switch
Device short name	9007MS/ML
Sensor design	Miniature
Body type	Fixed
Head type	Multi-directional head
Material	Metal
Body material	Cast zinc
Number of poles	1

### Complementary

Fixing mode	By the body
Movement of operating head	Multi-directional
Type of operator	Spring return wire whisker steel -
Type of approach	Multi-directional approach
Switch actuation	By any moving part
Contacts type and composition	NC-NO
Switch function	SPDT
Contact form	Form C
Contacts material	Silver contacts
Contact operation	Snap action
Positive opening	Without
Electrical connection	Pre-wired cable bottom
Type of cable	SJTO cable (AWG 18), 2.74 m, yellow
Terminals description ISO n°1	(black)com (red)NC (green-yellow)gnd (white)NO
Wire insulation material	PVC
Maximum force for tripping	15 ozf

<b>[Ie] rated operational current</b>	6 A at 120 V AC, A300 conforming to NEMA rating designation 3 A at 240 V AC, A300 conforming to NEMA rating designation 5 A at 28 V DC
<b>[Ithe] conventional enclosed thermal current</b>	10 A
<b>[Ui] rated insulation voltage</b>	300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14
<b>Electrical durability</b>	100000 cycles
<b>Mechanical durability</b>	10000000 cycles
<b>Marking</b>	CSA UL CE
<b>Sale per indivisible quantity</b>	1
<b>Height</b>	44.45 mm
<b>Width</b>	39.62 mm
<b>Depth</b>	15.75 mm
<b>Product weight</b>	0.54 kg

## Environment

<b>Shock resistance</b>	35 gn for 9 ms conforming to IEC 60068-2-27
<b>Vibration resistance</b>	10 gn (f= 75...1200 Hz) conforming to IEC 60068-2-6
<b>NEMA degree of protection</b>	NEMA 1 conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250
<b>IP degree of protection</b>	IP54 conforming to IEC 60529
<b>Ambient air temperature for operation</b>	-40...104 °C
<b>Ambient air temperature for storage</b>	-40...104 °C
<b>Protective treatment</b>	Epoxy powder coat
<b>Product certifications</b>	CSA CE UL
<b>Standards</b>	E78403 LR 25490 Class 32 11 03

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	6.1 cm
<b>Package 1 Width</b>	28.4 cm
<b>Package 1 Length</b>	30.2 cm
<b>Package 1 Weight</b>	567.0 g

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>

**California proposition 65**

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Contractual warranty**

Warranty 18 months

**Recommended replacement(s)**