

REL-SG220/B110 - Single relay



2960106

<https://www.phoenixcontact.com/us/products/2960106>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



KAMMRELAIS®, contact B 110, size 2, dry contact, 4 changeover contacts, input voltage 220 V DC

Commercial data

Item number	2960106
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	CK6192
Catalog page	Page 103 (IF-2002)
GTIN	4017918086510
Weight per piece (including packing)	30.04 g
Weight per piece (excluding packing)	28.1 g
Customs tariff number	85364900
Country of origin	DE

REL-SG220/B110 - Single relay



2960106

<https://www.phoenixcontact.com/us/products/2960106>

Technical data

Product properties

Product type	Single relay
Mechanical service life	approx. 10 ⁸ cycles

Electrical properties

Test voltage (Winding/contact)	500 V AC (50 Hz, 1 min., winding/contact)
Test voltage (Changeover contact/changeover contact)	500 V AC (50 Hz, 1 min., changeover contact/changeover contact)

Input data

Coil side

Nominal input voltage U_N	220 V DC
Input voltage range	176 V DC ... 242 V DC
Input voltage range in reference to U_N	0.8 ... 1.1
Typical response time	5 ms
Typical release time	6 ms
Coil resistance	25000 Ω \pm 15 %

Output data

Switching

Contact switching type	4 changeover contacts
Type of switch contact	Single contact
Contact material	Ag, gold-flashed
Maximum switching voltage	125 V AC 150 V DC
Limiting continuous current	2 A
Maximum inrush current	2 A
Interrupting rating (ohmic load) max.	48 W (at 24 V DC) 40 W (at 48 V DC) 40 W (at 60 V DC) 45 W (at 110 V DC) 50 VA (for 125 V AC)


Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Drawings

Circuit diagram



REL-SG220/B110 - Single relay

2960106

<https://www.phoenixcontact.com/us/products/2960106>



Classifications

ECLASS

ECLASS-11.0	27371601
-------------	----------

REL-SG220/B110 - Single relay



2960106

<https://www.phoenixcontact.com/us/products/2960106>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com