ATGBICS SFP-GIG-BX-D20 Alcatel Compatible Transceiver SFP 1000Base-BX-D (Tx1490nm/Rx1310nm, 10km, SMF, DOM)

Brand : ATGBICS Product code: SFP-GIG-BX-D20-C

Product name : SFP-GIG-BX-D20 Alcatel Compatible Transceiver SFP 1000Base-BX-D (Tx1490nm/Rx1310nm,

10km, SMF, DOM)

ATGRICS ATTENDA AND TO THE REST OF THE RES

SFP-GIG-BX-D20 Alcatel Compatible Transceiver SFP 1000Base-BX-D (Tx1490nm/Rx1310nm, 10km, SMF, DOM)

 $ATGBICS\ SFP-GIG-BX-D20\ Alcatel\ Compatible\ Transceiver\ SFP\ 1000Base-BX-D\ (Tx1490nm/Rx1310nm,\ 10km,\ SMF,\ DOM):$

ATGBICS SFP-GIG-BX-D20 1000Base-BX SFP supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of Tx1490nm/Rx1310nm via an LC connector. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of AlcatelSFP-GIG-BX-D20= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
SFP transceiver type * Fiber optic Maximum data transfer rate * 1250 Mbit/s Interface type * SFP Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Tx wavelength (max) Rx wavelength (max) Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM) I250 Mbit/s SFP Fiber optic A SFP A SFP A A SFP A A SFP A A SFP A A SFP SFP	1250 Mbit/s	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
	LC BX-D 10000 m 1490 nm	Operational conditions Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
	Weight & dimensions Width Depth Height	13.4 mm 56.5 mm 8.5 mm	
Features Product colour	Silver	Weight Packaging data	15 g
Housing material Plug and Play Hot-swap Easy to install Country of origin Brand compatibility Certification Metal	Number of products included Package type	1 pc(s) Box	
	Technical details Sustainability compliance Sustainability certificates Doesn't contain	√ RoHS Lead	



5056468717825

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.