



|                |  |            |  |                   |  |         |  |           |  |  |  |                               |    |  |
|----------------|--|------------|--|-------------------|--|---------|--|-----------|--|--|--|-------------------------------|----|--|
|                |  |            |  |                   |  | Dat.    |  | Name      |  | <p>All Dim. in mm<br/>Orig. Size DIN A 4</p> | D-Sub male standard 37 poles<br>with solder pins, screw-lock,<br>board lock and grounding pins | Maßstab/<br>Scale<br>1,5:1    |    |  |
|                |  |            |  |                   |  | Detail. |  | 26-OCT-01 |  |  |  |                               | JB |  |
|                |  |            |  |                   |  | Insp.   |  |           |  |  |  |                               |    |  |
|                |  |            |  |                   |  | Stand.  |  |           |  |  |  | Blatt/ Page<br>3              |    |  |
| 09 66 463 6813 |  | 4-40 UNC   |  | 2                 |  |         |  |           |  | TB 09 66 463 X81X                            |  |                               |    |  |
| 09 66 463 7813 |  | 4-40 UNC   |  | 3                 |  |         |  |           |  |  |  |                               |    |  |
| 09 66 463 5813 |  | 4-40 UNC   |  | 0,76 µm Au        |  | 29725   |  | 26-OCT-01 |  |  |  |                               | JB |  |
| Part number    |  | screw-lock |  | Performance level |  | Mod.    |  | Dat.      |  | Name   |  | HARTING EURL<br>F-95972 Paris |    |  |

