



DIM. A = 2.50 X No. of Spaces
 DIM. B = DIM. A + 5.00
 DIM. C = DIM. A + 3.60

* Available in 2 through 15 Circuits

Material:

- * Material: Nylon 46 UL 94V-0
- * Contact: Brass, round pins

Ordering Code:

CI25 ** P 1 V * 0 -LF
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
 1 = 3.05μm(120μ") Matte Tin
 over 0.76μm(30μ") Nickel
- ⑤ Tail Style: V= Straight
- ⑥ Color: 0=Nature ,1=Black ,3=Red
- ⑦ Other Option: 0= Standard
- ⑧ LF= For Lead Free IR Processes

Recommended P.C. Board Layout

RoHS Compliant

		DATE	UNIT: mm / inch	TITLE: 2.50MM(.098") STRAIGHT HEADERS	 瀚荃股份有限公司 CviLux Corporation						
		DRAWN BY: Jim	08/17-06'	TOLERANCE UNLESS OTHERWISE SPECIFIED							
		ENGINEER: Eisley	08/24-06'	.X ± 0.30/.012 X.* ± 1'							
		CHECKED BY: David	08/24-06'	.XX ± 0.20/.010 .X.* ±							
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	08/24-06'	.XXX ± 0.10/0.04 .XX.* ±	FINISH:	DRAWING NO. CI2516SA	PART NO. CI25**P1V*0-LF	SCALE 3 / 1	SHEET 1 OF 1