



used for: D-SUB COMBINATION

NOTES:

- 1. MATERIAL: COPPER ALLOY
- 2. PLATING:
 ITEM 1: min. 30µ" HARD GOLD OVER min. 50µ" NICKEL
 ITEM 2: min. 8µ" HARD GOLD OVER min. 50µ" NICKEL
 ITEM 3: NICKEL PLATED

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

		tolerance ISO 2768-m				scale: 5:1	
						material: SEE NOTES	
		2002		date		title:	
		drawn		26.07.		HIGH POWER CONTACT MALE (b) CRIMP / SOLDER VERSION 90° - 30A D-SUB COMBINATION	
		appd.		26.07.			
				name		dwg no: AutoCAD	
				E. Mickenbecker		DIN-A	
				norm		4	
				d-old		sh: 1/1	
2 x c		Ä 1615		21.08.2002		13K1A657	
1 x b		Ä 1603		08.08.2002			
rev.		description		date		part no: 131C16039X	
		name					

