

CP1500 Series Common Point Ground

Common point ground cords connect multiple aspects of an ESD workstation to ground.

Transforming Technologies CP1500 common point ground cord offers the common point ground required by ANSI/ESD S-6.1 and ANSI/ESD-S20.20.

The CP1518 classic common point ground are standard with two banana jacks, 10mm male snap, and a 1 meg resistor. The CP1518 includes a 15' long black PVC cord made with 7 strand tinsel wire to #10 ring terminal. It is also available with a large O-ring for military applications (CP1518BO) or with a bulldog clip and female snap (CP1518BD) for field service mats.

Meets or exceeds requirements of ANSI/ESD S20.20 and ANSI/ESD S-6.1.



CP1518

CP1518BO

CP1518BD

Features

- 10mm Snap for Connection to Surface
- 15' PVC Cord made with 7 strand tinsel
- #10 Ring Terminal for Solid Connection To Ground
- Available in Bulldog Clip or O-Ring Terminations

Specifications:

Cord Length: 15'

Resistor: CP1518: 1 meg
CP1518BD: 1 meg
CP1518BO: 0 Meg

Ground Terminal: #10 ring type

Wire Insulation: PU/PVC

Color: Black

Part Numbers:

CP1518 Classic CPG, 15' cord, 10mm Male, 1 meg

CP1518BO Classic CPG, 15' cord, 10mm Male, 0 meg, large O-ring (for military)

CP1518BD Classic CPG, 15' cord, 10mm female, 1 meg, Bulldog clip (for field service mats)

Applications:

Common point ground cords can be used to connect coil cords to a mat via the banana jacks, the ground cord to the mat via snap, and connect the mat to ground.

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.