



- 1 COPPER ALLOY PER ASTM B301
- 2 1.27 μm [50 μin] MIN GOLD PER ASTM B488
OVER 2.54 μm [100 μin] MIN NICKEL PER
QQ-N-290 ON ENTIRE STOCK.
- 3. APPLICATION TOOLING:
CRIMPING TOOL: M22520/23-01
DIE SET: M22520/23-02
LOCATOR: TYCO P/N 1738331-1
EXTRACTION TOOL: M81969/28-01
- 4. WIRE ACCOMMODATED: 8 AWG
STRIP LENGTH: 9.60 [.378] - 10.10 [.398]
- 5. THIS PRODUCT IS SOLD BY TYCO ELECTRONICS
UNDER A LICENSE FROM RADIAL SA

PRELIMINARY
NOT RELEASED FOR
PRODUCTION

Tyco PN - 1738019-1

DIMENSIONS : mm [inch]

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	22MAR2004	REV	0
DRAWN BY		CHK		Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS:		APPROVED		POWER CONTACT, PIN, CRIMP TERMINATION SIZE 5 GPR	
mm [INCHES]	TYCO STANDARD	PRODUCT SPEC		SIZE	00779
	TYCO SPECIFIED	APPLICATION SPEC		SCALE	1:1
0 P.L.C. =				SHEET	1 of 1
1 P.L.C. =				REV	0
2 P.L.C. =				CUSTOMER DRAWING	
3 P.L.C. =					
4 P.L.C. =					
5 P.L.C. =					
6 P.L.C. =					
7 P.L.C. =					
8 P.L.C. =					
9 P.L.C. =					
10 P.L.C. =					
11 P.L.C. =					
12 P.L.C. =					
13 P.L.C. =					
14 P.L.C. =					
15 P.L.C. =					
16 P.L.C. =					
17 P.L.C. =					
18 P.L.C. =					
19 P.L.C. =					
20 P.L.C. =					
21 P.L.C. =					
22 P.L.C. =					
23 P.L.C. =					
24 P.L.C. =					
25 P.L.C. =					
26 P.L.C. =					
27 P.L.C. =					
28 P.L.C. =					
29 P.L.C. =					
30 P.L.C. =					
31 P.L.C. =					
32 P.L.C. =					
33 P.L.C. =					
34 P.L.C. =					
35 P.L.C. =					
36 P.L.C. =					
37 P.L.C. =					
38 P.L.C. =					
39 P.L.C. =					
40 P.L.C. =					
41 P.L.C. =					
42 P.L.C. =					
43 P.L.C. =					
44 P.L.C. =					
45 P.L.C. =					
46 P.L.C. =					
47 P.L.C. =					
48 P.L.C. =					
49 P.L.C. =					
50 P.L.C. =					