

6 5 4 3 2 1

APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/12/20	
A		UPDATE DRAWING	4/7/21	LH/RC

RECOMMENDED PCB LAYOUT

SPECIFICATIONS:

Material:
 Insulator: PA66, rated UL 94V-0
 Insulator color: Green
 Screw: M2.5
 Contact: Copper Alloy, Tin plated.
 Electrical:
 Voltage rating: 300 VAC
 Current rating: 12 Amp
 Dielectric withstanding voltage: 1,600 VAC for 1 minut
 Mechanical:
 Torque: 0.4Nm
 Wire Range: 26-14 AWG
 Wire strip length: 5~6mm
 Environmental:
 Operating temperature: -40°C to +105°C
 Environmental:
 Lead free, RoHS compliant.

Poles: 2 thru 24
 A = .200 [5.08] X No. of Positions
 B = .200 [5.08] x No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	∅X	± .10
.XX	± .020	∅XX	± .015
.XXX	± .015	∅XXX	± .010

DRAWN	LH	11/12/20
CHECKED	RC	11/12/20
APPROVED		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH

909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

TITLE		EURO BLOCK, .200 [5.08] PITCH, 45 DEGREE ANGLE	
SIZE	PART NO.	REV.	
X	EB21A-XX-D-DA	A	
REF:	S00067C	SCALE:	NTS
		SHEET 1 OF 1	

6 5 4 3 2 1