



- 1 HOUSING MATERIAL: HIGH TEMPERATURE, GLASS-FILLED POLYMER
COLOR: GRAY OR WHITE
- 2 POST AND GROUND PLATE MATERIAL: BRASS.
- 3 POST FINISH: DIN 41612 CLASS 2 IN CONTACT AREA.
TIN-LEAD PLATE ON POSTS.
- 4 POST FINISH: DIN 41612 CLASS 3 IN CONTACT AREA.
TIN-LEAD PLATE ON POSTS.
- 5 RECOMMENDED HOLE SIZE FOR MANUAL APPLICATION OF
CONNECTOR ONTO PC BOARD.
- 6 GROUND PLATE FINISH: DIN 41612 CLASS 2 IN CONTACT AREA.
TIN-LEAD PLATE ON POSTS.
- 7 GROUND PLATE FINISH: DIN 41612 CLASS 3 IN CONTACT AREA.
TIN-LEAD PLATE ON POSTS.
- 8 GROUND PLATE FINISH: 0.00127 [0.000050] GOLD IN CONTACT AREA.
0.00127 [0.000050] NICKEL UNDERPLATE ALL OVER. TIN-LEAD PLATE ON POSTS.
- 9 POST FINISH: 0.00127 [0.000050] GOLD IN CONTACT AREA.
0.00127 [0.000050] NICKEL UNDERPLATE ALL OVER. TIN-LEAD PLATE ON POSTS.
- 10 MOLD REVISION DATE CODE MOLDED IN THIS AREA.
- 11 OBSOLETE PART NUMBER.

11	4	536146-9
	3	536146-5
	8	536146-1
	FINISH	ASSY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN L. BRINER 2/24/92	Tyco Electronics Corporation Harrisburg, PA 17105-3608																		
DIMENSIONS: INCHES		CHK: D.C. RUBENDALL 3/8/92	NAME: PIN ASSEMBLY, ENHANCED EUROCARD WITH TWO EXTERNAL PLATES																		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD: -	PRODUCT SPEC: -																		
<table border="1"> <tr><td>0 PLC</td><td>±</td><td>-</td></tr> <tr><td>1 PLC</td><td>±</td><td>-</td></tr> <tr><td>2 PLC</td><td>±</td><td>-</td></tr> <tr><td>3 PLC</td><td>±</td><td>0.13 [0.005]</td></tr> <tr><td>4 PLC</td><td>±</td><td>-</td></tr> <tr><td>ANGLES</td><td>-</td><td>-</td></tr> </table>		0 PLC	±	-	1 PLC	±	-	2 PLC	±	-	3 PLC	±	0.13 [0.005]	4 PLC	±	-	ANGLES	-	-	APPLICATION SPEC: -	
0 PLC	±	-																			
1 PLC	±	-																			
2 PLC	±	-																			
3 PLC	±	0.13 [0.005]																			
4 PLC	±	-																			
ANGLES	-	-																			
MATERIAL: HSG: Δ POST: Δ	FINISH: Δ GROUND PLATE: Δ	WEIGHT: -	SIZE: A1 CAGE CODE: 00779 DRAWING NO: 536146	RESTRICTED TO: -																	
CUSTOMER DRAWING		SCALE: 4:1	SHEET: 1 of 1	REV: G																	