



POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH IN/MM
3	1200271058	403007P03M020	6.56' +3.50" -0 [2.0M +88.9 -0]
3	1200271078	403007P03M050	16.40' +6.50" -0 [5.0M +165.1 -0]

CONNECTOR SPECIFICATION:

VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP68
OPERATING TEMPERATURE	-30°C TO +80°C
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	INSERT	POLYURETHANE (PUR)	BLACK
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	COUPLING NUT	BRASS	NICKEL PLATED
4	OVERMOLD	TPU	YELLOW
5	CABLE 0.25mm ² (25AWG) (COPPER STRANDING) 3 CONDUCT. 300V	JACKET: PUR	BLACK

DESCRIPTION EC NO.: WEU2010-0311 DRWN: REISSNER 2010/01/28 CHKD: FP APPR: NSTAUDIG 2010/02/01 REV 1	QUALITY SYMBOLS ▽ = 0 ▽ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM	SCALE 2:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		mm	INCH						
		4 PLACES	±---	±---	DRAWN BY REISSNER	DATE 2010/01/28	NC 3P M 90 24AWG PUR ----		
		3 PLACES	±---	±---	CHECKED BY FP	DATE 2010/01/28			
2 PLACES	±---	±.01	APPROVED BY NSTAUDIG	DATE 2010/02/01	MOLEX INCORPORATED MOLEX				
1 PLACE	±0.3	±---	MATERIAL NO.					DOCUMENT NO. SD-120027-007	SHEET NO. 1
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				