

Mandatory sign - US-PML-M100 (D50) - 1014176

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Mandatory sign, Card, blue, Unlabeled, Can be labeled with: THERMOMARK CARD PLUS, THERMOMARK CARD: Blank, Mounting type: Adhesive, Diameter: 50 mm, Lettering field: d: 50 mm

Product Features

- UniSheet - stick-on mandatory signs, color preprinted, without symbol
- Suitable for indoor and outdoor use
- The mandatory signs conform to the ISO 7010 international standard
- Highly flexible, plasticized PVC labels which are ideal for uneven surfaces

Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| Weight per Piece (excluding packing) | 6.0 GRM |
| Custom tariff number | 39203000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|-----------|----------|
| Width (a) | 50 mm |
| Diameter | 50.00 mm |

Ambient conditions

| | |
|---------------------------------|--|
| Ambient temperature (operation) | -40 °C ... 90 °C |
| Ambient temperature (assembly) | > 8 °C |
| Recommended storage conditions | 4 - 40°C Storage in a cool and dark place in the original packaging is recommended. |

General

| | |
|------------|---------------|
| Color | blue |
| Design | Round |
| Components | Silicone-free |

Mandatory sign - US-PML-M100 (D50) - 1014176

Technical data

General

| | |
|--|-------------------------------------|
| Material | PVC |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Printing | Blank |
| Number of individual labels | 4 |
| Adhesive | Acrylic |
| Device | 5146464 THERMOMARK CARD |
| | 5146481 THERMOMARK CARD PLUS |
| Ink ribbon | 1014402 TM-RIBBON 110-TC/TR WH |
| | 5146451 THERMOMARK CARD-US-MAG1 |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN 60068-2-11:2000-02 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | Following DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result | Test passed |
| Foil strength | 50 µm |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27141199 |
| eCl@ss 4.1 | 27141199 |
| eCl@ss 5.0 | 27371301 |
| eCl@ss 5.1 | 27371301 |
| eCl@ss 6.0 | 27371301 |
| eCl@ss 7.0 | 27371301 |
| eCl@ss 8.0 | 27371301 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000712 |
| ETIM 4.0 | EC002498 |

Mandatory sign - US-PML-M100 (D50) - 1014176

Classifications

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC000761 |
|----------|----------|

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172501 |
| UNSPSC 7.0901 | 43212107 |
| UNSPSC 11 | 43172501 |
| UNSPSC 12.01 | 43212107 |
| UNSPSC 13.2 | 43212107 |

Accessories

Accessories

Ink ribbon

Ink ribbon - TM-RIBBON 110-TC/TR WH - 1014402



Ink ribbon, Length: 240000 mm, Color: white

Magazine

Magazine - THERMOMARK CARD-US-MAG1 - 5146451



Magazine for the THERMOMARK CARD printer, for accommodating US cards