


WIRING INFORMATION

	J1	Wire color	J2
X	2-e	Rose	2-e
	1-e	Orange	1-e
X	2-d	Yellow	2-d
	1-d	Rose	1-d
X	2-c	Rose	2-c
	1-c	Brown	1-c
X	2-b	Black	2-b
	1-b	Rose	1-b
X	2-a	Rose	2-a
	1-a	Red	1-a
	Shell	Braid	Shell



33 27 242 250 0021	25 m
33 27 242 200 0021	20 m
33 27 242 150 0021	15 m
33 27 243 150 0002	1.5 m
33 27 243 700 0019	7 m
33 27 242 120 0055	12 m
33 27 243 350 0029	3.5 m
33 27 243 400 0028	4 m
33 27 243 300 0027	3 m
33 27 243 060 0026	0.6 m
33 27 242 100 0021	10 m
33 27 243 800 0020	8 m
33 27 243 650 0019	6.5 m
33 27 243 200 0003	2 m
33 27 243 100 0002	1 m
33 27 243 050 0001	0.5 m
<i>Part-No.</i>	<i>Dim. L</i>

NOTES /

- CABLE ASSEMBLY IS MANUFACTURED PER RELEVANT JOB.
- MECHANICAL REQUIREMENTS
 - OPERATING TEMPERATURE = -20° TO +105°C
 - MATING CYCLES : 250, PERFORMANCE LEVEL 2 (IEC 60512-5)
- THE CONNECTOR COMPLIES REQUIREMENT : IEC 61076-4-107
- WHITE LABEL INFORMATION:

DATE CODE
HARTING P/N
- CABLE MUST BE PERFORMED HI-POT TEST AND CONTINUITY TEST
- CABLE MUST BE PACKED INTO A PLASTIC BAG.

Rev.	Description	Appr.	Date
C	Add length 20m & 25m via CRZ2274	Ivy Lin	09/12/21
B	Add length 1.5m & 15m via CRZ2259	Ivy Lin	20/10/21
A	Prototype	Lucy Zheng	28/06/17

All rights reserved Department HCS - CN HARTING Customised Solutions D-32339 Espelkamp	All Dimensions in mm Original Size DIN A3	Scale / Free size tol. /	Ref. / Sub. /
	Created by LINI Inspected by LIANL Standardisation LIANL Date 2021-12-09 State Final release	Title Har-link standard cable,male double ended cable assy, L=*M Doc-Key / ECM-Nr. /	
Type TB Number 33 27 0001			